

# DEALER HOT WATER PRESSURE WASHERS

## Portable Gasoline

### Direct/Belt Drive | DHG Series



The 12V hot water gas pressure washer series may be compact but it is capable of cleaning the toughest grime. Completely portable, this 4000 PSI unit features a 12V Beckett burner with a 4-pancake bottom-fired heat exchanger.



DHG-4004-D0H6G  
Direct Drive

#### Pump

- Direct or belt drive triplex piston General pump with ceramic plungers
- Stainless-steel and brass unloader valve, adjustable
- Forged brass manifold
- Thermal relief valve

#### Engine

- Performance proven engine with low-oil protection
- 12V electric start (battery not included)

#### Frame

- Reinforced powder coated steel tube frame with center balanced lifting hook
- 15-inch pneumatic tires

#### Components

- 1/2-inch schedule 80 pipe coil with 4-pancake bottom-fired heat exchanger
- 12V Beckett burner
- No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)
- Adjustable thermostat
- Hour meter
- 250°F steam

#### Miscellaneous

- Temperature rise 130°F/54°C above ambient, maximum outlet temperature is 210°F
- Water output temperature is 250°F in "wet" steam

#### Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 1/4-inch MEG and 1/4-inch MQC wet steam nozzle – 25°
- 50-foot x 3/4-inch steel wire-braided high pressure hose with quick connects, swivel and bend restrictors
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off

DHG-4004-B0H6G  
Belt Drive shown with  
stainless-steel coil wrap  
option, HX-0273



# DEALER HOT WATER PRESSURE WASHERS

## Portable Gasoline

### Direct/Belt Drive | DHG Series



**Direct Drive**

Model Number	PSI	GPM	Displacement/Engine	Pump	Gas Tank Capacity	Burner Fuel Tank Capacity	Burner Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
DHG-4004-D0H6G	4000	3.7	389cc Honda GX390 OHV	General	1.61 gallons	10.0 gallons	2.14 gph	299,600	57.5x35.5x59.5in.	601 lb.	478 lb.

**Belt Drive**

Model Number	PSI	GPM	Displacement/Engine	Pump	Gas Tank Capacity	Burner Fuel Tank Capacity	Burner Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
DHG-4004-B0H6G	4000	3.7	389cc Honda GX390 OHV	General	1.61 gallons	10.0 gallons	2.14 gph	299,600	57.5x35.5x59.5in.	643 lb.	520 lb.

**Options:**

Part Number	Description	Fits Models
HX-0278	Skid feet - Stationary applications	All models
HX-0273	Stainless-steel coil wrap - Converts powder coated painted coil wrap to stainless-steel material	All models

**Accessories:**

Part Number	Description	Fits Models
50-0195	Hose reel - 13-inch, 150-foot maximum hose length	All models
50-0196	Hose reel - 16-inch, 200-foot maximum hose length	All models
AW-8400-0021	Low pressure detergent injector - Allows the user to apply the recommended detergents	All models

POWERED by **HONDA**™