

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve								
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
598	STD	04-44	54-02	228	236	184	188	.235	.227	.470	.454	.012	.012	HYD	HYD	112	116	
704	STD	05-55	55-04	240	238	195	189	.242	.227	.484	.454	.014	.014	HYD	HYD	115	115	
599	1	09-55	52-07	243	238	198	192	.266	.254	.532	.508	.016	.016	HYD	HYD	112	116	*STD SPRINGS AND COMPUTER OK
744	2	16-64	64-16	260	260	207	207	.258	.258	.516	.516	.030	.030	HYD	HYD	114	114	*STD SPRINGS AND COMPUTER OK
766	3	25-64	66-25	269	271	216	216	.260	.262	.520	.524	.044	.044	HYD	HYD	110	110	*SPRINGS PLUS COMPUTER REQUIRED
760	4	32-70	70-32	282	282	228	228	.275	.275	.550	.550	.064	.064	HYD	HYD	112	108	**SPRINGS PLUS COMPUTER REQUIRED
761	5	35-75	75-35	290	290	240	240	.285	.285	.570	.570	.082	.082	HYD	HYD	112	108	**SPRINGS PLUS COMPUTER REQUIRED

CODE: FORD EA EB ED EF
 REGRIND - 46GOHC
 BILLET - EPEA
 EXCHANGE - DEP EA

NOTES: 1. PRELOAD SHOULD BE CHECKED AND ADJUSTED

*SINGLE SPRING WITH DAMPER #7739-12

****761** SPECIAL PISTONS WITH DEEPER VALVE POCKET
 RELIEFS ARE REQUIRED
 +VALVE SPRING #7333-12(DOUBLES)

EA - EB - ED - EF - EL

ROCKER RATIO 2 : 1

FORD