



FLEETCLEAN SYSTEMS LLC

401.356.4156

www.fleetcleansystems.com
sales@fleetcleansystems.com

Specifications

ATTRIBUTE	DESCRIPTION
Physical Form	Blue Liquid
Odor	Pungent Acidic
Solubility	Complete in Water
Foam	Moderate
Viscosity	Water like
pH (Typical)	2.5 - 3.5
Flash Point	Not Applicable

Dilution Ratios

Use	Dilution
Heavy	6:1 - 8:1
Moderate	10:1 - 20:1
Light	20:1 - 30:1

Available In

PART #	SIZE
01BF130	5 Gal.
01BF131	55 Gal.
01BF132	275 Gal.



FCS #1B-F

Tech Data Sheet

FCS #1B is a low pH pre-soak to be used as a step 1 in a 2 step brushless wash program. An aggressive cleaner with a foaming agent for non-polished aluminum fleets. The foaming agent increases the ability to break down the bond of road film and brightens non-polished aluminum leaving a silver satin look.

Benefits

- ◆ Safe on painted surfaces
- ◆ Helps remove difficult magnetic road film without brushing
- ◆ Foaming Agent increases soaps effectiveness against road film.

Applications

- ◆ Brightens and whitens non-polished aluminum
- ◆ Use as a pre-soak in 2 Step fleet brushless fleet cleaning for enhanced road film removal

Precautions

- ◆ **CONTAINS HYDROFLUORIC AND PHOSPHORIC ACIDS. PERSONAL PROTECTION EQUIPMENT SHOULD BE WORN WHEN HANDLING**
- ◆ **DO NOT USE ON POLISHED OR ANODIZED ALUMINUM**
- ◆ **DO NOT ALLOW TO DRY ON GLASS OR ANY SURFACE**

Note: Cleaning effectiveness is affected by: temperature, concentration, dwell time, water hardness, and soap application pressure. Soap concentration may be adjusted to compensate for changes in these conditions.