DEALER HOT WATER PRESSURE WASHERS
Stationary Natural Gas/LP
Belt Drive | HEG Series

Designed to accommodate and clean heavily soiled vehicles and industrial equipment this system is perfect for a wash bay set up. Efficient and rugged, the HEG Series is one of the best on the market.





HEG-2004-0E2G

Pump
- *Belt drive triplex piston General pump with ceramic plungers*
- *Thermal relief valve*

Motor
- *Open drip-proof electric motor with manual thermal overload protection*

Frame
- *Powder coated steel frame with removable side panels*

Components
- *½-inch schedule 80 pipe coil heat exchanger*
- *Natural gas or LP gas-fired (vapor only) natural draft with aspirating-type burner, 10-inch draft diverter*
- *24V control system*
- *Adjustable thermostat*
- *Pressure switch and over-pressure safety controls*
- *Polyethylene float tank (4-gallon with in-line screen filter)*
- *Electronic ignition with standing pilot light*

Miscellaneous
- *Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F (250°F/121°C outlet temperature with steam option)*

Unit Includes:
- *Quick connect nozzles - 0°, 15°, 25°, 40° and fixed detergent nozzle*
- *50-foot x ⅜-inch steel wire-braided high pressure hose*
- *Adjustable pressure insulated dual lance with fixed detergent nozzle*
- *Professional-grade insulated trigger gun with safety lock-off*

NATURAL GAS INSTALLATION RECOMMENDATION:

This natural gas pressure washer must have a clearance of 2-feet on all sides of the unit and 4-feet above the unit.

Gas Supply Line:

Natural Gas
7- to 8-inch water column input

LP Gas
12- to 14-inch water column input

Recommended Pipe Sizes for Gas Supply Line:

Natural Gas		LP Gas	
Distance to Unit from Regulator	*Pipe Size*	*Distance to Unit from Regulator*	*Pipe Size*
0-feet to 50-feet	1½-inch 1PS	0-feet to 50-feet	1½-inch 1PS
50-feet to 100-feet	2-inch 1PS	50-feet to 100-feet	1½-inch 1PS
100-feet to 200-feet	2½-inch 1PS	100-feet to 200-feet	1¾-inch 1PS

Exclusive Dealer Product

CSA CERTIFIED

Made in USA with Globally Sourced Components

FleetClean Systems LLC • 1 Tupperware Drive Suite #3, North Smithfield, RI 02896 • (401) 356-4156 • www.fleetcleansystems.com

DEALER HOT WATER PRESSURE WASHERS

Stationary Natural Gas/LP

Belt Drive | HEG Series

Model Number	*PSI*	*GPM*	*Horsepower/Motor*	*Natural Gas BTU per hour*	*LP Gas BTU per hour*	*Dimensions (LxWxH)*	*Ship Wt.*	*Net Wt.*
HEG-1805-0E2G	1800	4.7	6.0 HP, 230V, 1Ø, 25.5A	338,000	326,000	56.5x29x49.75in.	844 lb.	724 lb.
HEG-1805-0E3G	1800	4.7	6.0 HP, 230V, 3Ø, 16.0A	338,000	326,000	56.5x29x49.75in.	844 lb.	724 lb.
HEG-1805-0E4G	1800	4.7	6.0 HP, 460V, 3Ø, 8.0A	338,000	326,000	56.5x29x49.75in.	844 lb.	724 lb.
HEG-1805-0E8G	1800	4.7	6.0 HP, 208V, 1Ø, 28.2A	338,000	326,000	56.5x29x49.75in.	844 lb.	724 lb.
HEG-1805-0E9G	1800	4.7	6.0 HP, 208V, 3Ø, 18.5A	338,000	326,000	56.5x29x49.75in.	844 lb.	724 lb.
HEG-2004-0E2G	2000	4.2	6.0 HP, 230V, 1Ø, 25.5A	338,000	326,000	56.5x29x49.75in.	844 lb.	724 lb.
HEG-2004-0E3G	2000	4.2	6.0 HP, 230V, 3Ø, 16.0A	338,000	326,000	56.5x29x49.75in.	844 lb.	724 lb.
HEG-2004-0E4G	2000	4.2	6.0 HP, 460V, 3Ø, 8.0A	338,000	326,000	56.5x29x49.75in.	844 lb.	724 lb.
HEG-2004-0E8G	2000	4.2	6.0 HP, 208V, 1Ø, 28.2A	338,000	326,000	56.5x29x49.75in.	844 lb.	724 lb.
HEG-2004-0E9G	2000	4.2	6.0 HP, 208V, 3Ø, 18.5A	338,000	326,000	56.5x29x49.75in.	844 lb.	724 lb.
HEG-3004-0E2G	3000	3.9	8.0 HP, 230V, 1Ø, 37.0A	338,000	326,000	56.5x29x49.75in.	878 lb.	758 lb.
HEG-3004-0E3G	3000	3.9	8.0 HP, 230V, 3Ø, 20.0A	338,000	326,000	56.5x29x49.75in.	878 lb.	758 lb.
HEG-3004-0E4G	3000	3.9	8.0 HP, 460V, 3Ø, 10.0A	338,000	326,000	56.5x29x49.75in.	878 lb.	758 lb.
HEG-3004-0E5G	3000	3.9	8.0 HP, 575V, 3Ø, 8.0A	338,000	326,000	56.5x29x49.75in.	878 lb.	758 lb.
HEG-3004-0E8G	3000	3.9	8.0 HP, 208V, 1Ø, 40.5A	338,000	326,000	56.5x29x49.75in.	878 lb.	758 lb.
HEG-3004-0E9G	3000	3.9	8.0 HP, 208V, 3Ø, 23.0A	338,000	326,000	56.5x29x49.75in.	878 lb.	758 lb.
HEG-3005-0E2G	3000	4.8	10.0 HP, 230V, 1Ø, 44.0A	338,000	326,000	56.5x29x49.75in.	878 lb.	758 lb.
HEG-3005-0E3G	3000	4.8	10.0 HP, 230V, 3Ø, 25.0A	338,000	326,000	56.5x29x49.75in.	878 lb.	758 lb.
HEG-3005-0E4G	3000	4.8	10.0 HP, 460V, 3Ø, 12.5A	338,000	326,000	56.5x29x49.75in.	878 lb.	758 lb.
HEG-3005-0E5G	3000	4.8	10.0 HP, 575V, 3Ø, 10.0A	338,000	326,000	56.5x29x49.75in.	878 lb.	758 lb.
HEG-3005-0E8G	3000	4.8	10.0 HP, 208V, 1Ø, 48.7A	338,000	326,000	56.5x29x49.75in.	878 lb.	758 lb.
HEG-3005-0E9G	3000	4.8	10.0 HP, 208V, 3Ø, 29.0A	338,000	326,000	56.5x29x49.75in.	878 lb.	758 lb.

Options:

Part Number	*Description*	*Fits Models*
HX-0104	**K7 unloader; flow activated (Auto start/stop N/A)** - Converts pressure trapping unloader system to flow actuated K7 unloader	HEG-3004 models
HX-0105	**Liquid propane (Vapor only)** - Converts natural gas pressure washer to operate on liquid propane (vapor only)	All models
HX-0106	**Hour meter** - Displays the number of hours unit has been in operation	All models
HX-0107*	**Time delay shutdown** - Timer will shut off automatically when trigger gun is released and timer reaches setting	All models
HX-0108*	**(1) Remote station (Auto start/stop N/A)** - Adds control box which may be mounted away from unit to control on/off, burner and soap injection	All models
HX-0109*	**Time delay shutdown and first remote box** - Timer will shut off automatically when trigger gun is released and timer reaches setting; adds control box which may be mounted away from unit to control on/off, burner and soap injection	All models
HX-0110	**Additional remotes (up to 3)** - Additional remotes that may be added to the unit after the first remote is installed	All models
HX-0111	**Auto start/stop** - When trigger gun is released timer will turn unit off; when trigger gun is pulled, unit will restart	All models
HX-0112	**K7 unloader; flow activated (Auto start/stop N/A)** - Converts pressure trapping unloader system to flow actuated K7 unloader	All models except HEG-3004 models
HX-0113	**Dual gun** - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure	HEG-1805 models
HX-0114	**Dual gun** - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure	HEG-3005 models
HX-0115	**Stainless-steel access panels** - Converts powder coated painted access panels to stainless-steel material	All models
HX-0116	**Stainless-steel coil wrap** - Converts powder coated painted coil wrap to stainless-steel material	All models
HX-0117	**Painted box kit** - Adds painted side and end panels	All models
HX-0118	**Painted and stainless-steel box kit** - Adds stainless-steel side panels and painted end panels	All models
HX-0119	**250°F steam** - Steam option increases outlet temperature to 250°F; adds steam nozzle	HEG-1805 models
HX-0120	**250°F steam** - Steam option increases outlet temperature to 250°F; adds steam nozzle	HEG-2004 models
HX-0121	**250°F steam** - Steam option increases outlet temperature to 250°F; adds steam nozzle	HEG-3004 models
HX-0122	**250°F steam** - Steam option increases outlet temperature to 250°F; adds steam nozzle	HEG-3005 models
HX-0124	**Auto start/stop and first remote** - When trigger gun is released timer will turn unit off; when trigger gun is pulled, unit will restart; adds control box which may be mounted away from unit to control on/off, burner and soap injection	All models
HX-0154	**All stainless-steel frame and hardware on modular units** - Converts powder coated painted frame and hardware to stainless-steel material	All models
HX-0216	**Elevated float tank, 4.0 GPM** - Float tank is located at the back of the unit	HEG-2004 & HEG-3004 models
HX-0217	**Elevated float tank, 5.0 GPM** - Float tank is located at the back of the unit	HEG-1805 & HEG-3005 models

** You cannot order HX-0107 and HX-0108 together, you will need to order HX-0109 instead. HX-0107 and HX-0108 can be ordered separately. See photo of HX-0108 below.*



*HX-0108 Optional Remote Station