

DEALER HOT WATER PRESSURE WASHERS

Portable Electric Belt Drive | HHB Series



The belt driven HHB Series is designed for heavy-duty industrial cleaning jobs requiring hot water. It can easily handle the demanding jobs on construction jobsites, agricultural locations or commercial cleaning applications.



Pump

- Belt drive triplex piston AR plunger pump
- Adjustable high pressure detergent injector

Motor

- Open drip-proof electric motor with thermal overload protection
- 35-foot power cord

Frame

- Wrinkle-finish powder coated steel frame assembly
- 13-inch flat-free tires with rear tire brake

Components

- Stainless-steel coil wrap heat exchanger with horizontal schedule 80 pipe coil
- No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)
- Racor fuel/water separator
- Adjustable thermostat
- Polyethylene float tank with inlet filter screen
- 10-gallon polyethylene fuel tank

Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

Unit Includes:

- Quick connect nozzles – 0°, 15°, 25°, 40° and low pressure nozzle (except on HHB-303-0E1A)
- 50-foot x 3/8-inch high pressure hose with quick connects (50-foot steam hose on HHB-303-0E1A)
- Adjustable pressure insulated dual lance (except on HHB-303-0E1A)
- Single lance with dual insulated grips; steam nozzle (HHB-303-0E1A)
- Insulated trigger gun with safety lock-off



HHB-1502-0E1A



DEALER HOT WATER PRESSURE WASHERS

Portable Electric Belt Drive | HHB Series



Model Number	PSI	GPM	Horsepower/Motor	Plug Type	Burner Fuel Tank Capacity	Burner Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HHB-1002-0E1A	1000	2.0	1.5 HP, 115V, 1Ø, 16.2A	NEMA 5-20P	10.0 gallons	1.23 gph	172,200	57x30x41.5in.	606 lb.	486 lb.
HHB-1003-0E1A	1000	2.8	2.0 HP, 115V, 1Ø, 20.0A	NEMA 5-20P	10.0 gallons	1.84 gph	257,600	57x30x41.5in.	610 lb.	490 lb.
HHB-1502-0E1A	1500	1.8	2.0 HP, 115V, 1Ø, 19.9A	NEMA 5-20P	10.0 gallons	1.23 gph	172,200	57x30x41.5in.	610 lb.	490 lb.
HHB-2503-0E2A	2500	2.8	6.0 HP, 230V, 1Ø, 28.0A	NEMA 6-30P	10.0 gallons	1.84 gph	257,600	57x30x41.5in.	650 lb.	540 lb.
HHB-303-0E1A*	300	2.5	1.5 HP, 115V, 1Ø, 12.5A	NEMA 5-15P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	480 lb.	460 lb.

*Steam unit



NEMA 5-15P,
15-amp plug



NEMA 5-20P,
20-amp plug



NEMA 6-30P,
30-amp plug