

# WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
127	1	31-65	66-35	276	281	214	215	.265	.262	.385	.379	.052	.047	.012	.014	106	108	
107	2	32-68	68-30	280	278	228	227	.295	.295	.424	.424	.065	.058	.018	.018	108	108	
212	3	35-72	73-34	287	287	230	230	.277	.277	.400	.400	.065	.060	.015	.015	108	110	
215	4	32-75	76-31	287	287	243	240	.292	.292	.423	.420	.075	.073	.015	.018	113	111	
104	5	47-78	80-48	305	308	251	254	.325	.330	.467	.473	.104	.104	.020	.022	105	108	
250	6	40-84	86-44	304	310	255	259	.325	.330	.467	.473	.109	.109	.020	.022	107	109	
120	7	47-90	83-47	317	310	265	264	.355	.350	.510	.503	.105	.095	.022	.022	110	109	
439	1	36-70	72-36	286	288	215	219	.295	.295	.430	.428	.048	.045	.012	.014	108	112	
216	2	30-67	75-29	279	286	226	227	.275	.275	.397	.397	.053	.048	.015	.015	111	112	
667	3	30-67	64-30	277	274	231	230	.323	.323	.470	.472	.070	.065	.014	.012	106	107	
601	4	30-75	83-30	285	293	239	249	.333	.346	.487	.505	.075	.075	.012	.014	112	116	
213	5	38-70	70-36	288	288	243	243	.277	.277	.400	.397	.085	.075	.015	.018	107	107	
242	6	50-60	90-48	290	317	243	260	.325	.325	.472	.472	.110	.110	.015	.015	98	107	
213	7	38-70	70-36	288	288	243	243	.277	.277	.400	.397	.085	.075	.015	.018	107	107	
214	9	42-78	76-40	300	296	247	246	.295	.295	.427	.427	.090	.085	.015	.015	107	107	
467	10	34-63	73-32	277	285	249	258	.360	.365	.514	.521	.113	.092	.026	.026	106	110	
654	11	40-71	58-40	291	278	251	243	.318	.318	.459	.457	.113	.113	.018	.020	103		
164	12	38-85	90-38	303	308	253	251	.320	.320	.455	.455	.078	.072	.025	.025	113	114	

**CODE: HOLDEN 6 SOLID**  
 PERFORMANCE - 46G  
 STANDARD - 46S  
 BILLET - EP35  
 EXCHANGE - DEP H6

**6 SOLID**

**ROCKER RATIO 1.5**

***HOLDEN***