

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
229		23-56	62-21	259	263	196	196	.242	.243	.387	.389	.028	.022	HYD	HYD	106	112	STD RED
656	1	16-55	67-15	252	257	195	202	.268	.260	.429	.416	.023	.020	HYD	HYD	110	112	TORQUE & ST 1 GAS
521	2	27-67	72-29	274	282	202	207	.265	.265	.424	.424	.035	.032	HYD	HYD	110	110	ST2 GAS
408	2	26-63	68-24	270	272	208	209	.280	.280	.448	.448	.040	.037	HYD	HYD	109	110	
737	3	30-68	69-28	277	277	215	214	.294	.294	.470	.470	.048	.042	HYD	HYD	109	109	
409	3	30-70	70-30	280	280	217	217	.285	.285	.456	.456	.052	.048	HYD	HYD	108	111	
545	4	34-70	74-32	285	285	222	222	.290	.290	.464	.464	.055	.050	HYD	HYD	109	110	
410	5	38-78	78-38	295	295	226	226	.305	.305	.488	.488	.060	.055	HYD	HYD	109	111	
ALTERNATE GRINDS																		
401		25-71	63-23	276	266	204	204	.276	.276	.442	.442	.034	.030	HYD	HYD	110	110	
228		27-66	66-25	270	270	208	208	.295	.295	.472	.472	.040	.037	HYD	HYD	109	111	
563		39-75	81-73	295	298	219	219	.286	.286	.458	.458	.050	.045	HYD	HYD	108	112	
218		35-75	75-35	290	290	225	225	.278	.278	.445	.445	.067	.060	HYD	HYD	108	108	
474		36-80	82-33	294	295	224	234	.310	.324	.496	.518	.060	.055	HYD	HYD	109	114	
197		32-70	70-30	280	280	230	230	.320	.320	.512	.512	.060	.058	HYD	HYD	108	111	
757		33-73	74-33	286	287	230	231	.310	.310	.496	.496	.065	.065	HYD	HYD	110	110	
219		40-80	80-40	300	300	241	241	.300	.300	.480	.480	.075	.070	HYD	HYD	107	111	
417		43-81	77-41	304	298	241	240	.333	.333	.533	.533	.086	.083	HYD	HYD	111	108	
606		68-78	80-68	327	328	249	256	.330	.340	.528	.544	.095	.092	HYD	HYD	103	113	

CODE: HOLDEN V8 HYD

PERFORMANCE - 48G
 STANDARD - 48S
 BILLET - EP5
 EXCHANGE - DEP 253/308

NOTES: EFI MOTOR ON DIFFERENT SHEET
 SUIT RED, BLUE & BLACK

V8 HYD

ROCKER RATIO 1.6

HOLDEN