

VALVES



1/4" - 1" POLY MICRO VALVES

FEATURES

- 90° rotating handle
- Precision molded polypropylene is reinforced with fiberglass for additional strength.
- Standard FKM seats and O-Rings except 1". 1" has PTFE seats and O-Rings.

JG John Guest®
Fitting

The brand "John Guest" is a registered trademark of John Guest International Limited.



MICRO VALVES

| PART NO | DESCRIPTION | MAX PSI | THREAD SIZE | OPENING THRU BALL | QTY |
|----------|-----------------------------|---------|-------------|-------------------|-----|
| LV025V | 1/4" FEMALE NPT MICRO VALVE | 300 | 1/4" | 3/8" | 1 |
| LV038V | 3/8" FEMALE NPT MICRO VALVE | 300 | 3/8" | 3/8" | 1 |
| LV050V | 1/2" FEMALE NPT MICRO VALVE | 300 | 1/2" | 15/32" | 1 |
| LV050SLV | 1/2" SIDE LOAD MICRO VALVE | 300 | 1/2" | 1/2" | 1 |

MICRO VALVES

| PART NO | DESCRIPTION | MAX PSI | THREAD SIZE | OPENING THRU | QTY |
|----------|----------------------------|---------|-------------|--------------|-----|
| LVHB025V | 1/4" HOSE BARB MICRO VALVE | 300 | 1/4" | 3/8" | 1 |
| LVHB038V | 3/8" HOSE BARB MICRO VALVE | 300 | 3/8" | 3/8" | 1 |
| LVHB050V | 1/2" HOSE BARB MICRO VALVE | 300 | 1/2" | 3/8" | 1 |
| LVHB075V | 3/4" HOSE BARB MICRO VALVE | 300 | 3/4" | 15/32" | 1 |

MICRO VALVES

| PART NO | DESCRIPTION | MAX PSI | THREAD SIZE | OPENING THRU BALL | QTY |
|-------------|---|---------|-------------|-------------------|-----|
| LV025MTV | 1/4" FEMALE X MALE NPT MICRO VALVE | 300 | 1/4" | 3/8" | 1 |
| LV038MTV | 3/8" FEMALE X MALE NPT MICRO VALVE | 300 | 3/8" | 3/8" | 1 |
| LV038050MTV | 3/8" FEMALE X 1/2" MALE NPT MICRO VALVE | 300 | 3/8" x 1/2" | 3/8" | 1 |
| LV050MTV | 1/2" FEMALE X MALE NPT MICRO VALVE | 300 | 1/2" | 15/32" | 1 |
| LV050100MTV | 1/2" FEMALE X 1" MALE NPT MICRO VALVE | 300 | 1/2" | 15/32" | 1 |

MICRO VALVES

| PART NO | DESCRIPTION | MAX PSI | THREAD SIZE | OPENING THRU BALL | QTY |
|---------------|--|---------|-------------|-------------------|-----|
| LVHB038050MTV | 3/8" HOSE BARB X 1/2" MALE NPT MICRO VALVE | 300 | 1/2" | 3/8" | 1 |
| LVHB075MTV | 3/4" HOSE BARB X 3/4" MALE NPT MICRO VALVE | 300 | 3/4" | 1/2" | 1 |
| LVHB075100MTV | 3/4" HOSE BARB X 1" MALE NPT MICRO VALVE | 300 | 1" | 15/32" | 1 |

MICRO VALVES

| PART NO | DESCRIPTION | MAX PSI | THREAD SIZE | OPENING THRU BALL | QTY |
|----------------|--|---------|-------------|-------------------|-----|
| LVPL038MPTV | 3/8" FEMALE PUSH LOCK X 3/8" NPT MICRO VALVE FKM | 150 | 3/8" | 3/8" | 1 |
| LVPL038025MPTV | 3/8" FEMALE PUSH LOCK X 1/4" NPT MICRO VALVE FKM | 150 | 1/4" | 3/8" | 1 |

MICRO VALVES

| PART NO | DESCRIPTION | MAX PSI | THREAD SIZE | OPENING THRU BALL | QTY |
|----------|-----------------------------------|---------|-------------|-------------------|-----|
| LVPL025V | 1/4" FEMALE PUSH LOCK MICRO VALVE | 150 | 1/4" | 3/8" | 1 |
| LVPL038V | 3/8" FEMALE PUSH LOCK MICRO VALVE | 150 | 3/8" | 3/8" | 1 |
| LVPL050V | 1/2" FEMALE PUSH LOCK MICRO VALVE | 150 | 1/2" | 15/32" | 1 |

MICRO VALVES

| PART NO | DESCRIPTION | MAX PSI | THREAD SIZE | OPENING THRU BALL | QTY |
|---------|-------------------------|---------|-------------|-------------------|-----|
| MLV100V | 1" MANIFOLD MICRO VALVE | 300 | 1" | 1/2" | 1 |



1/2" - 2" 4 BOLTED VALVES



V100FP

V125

V200

4 BOLTED VALVES

| PART NO | DESCRIPTION | MAX PSI | PIPE SIZE | OPENING THRU | QTY | REPLACEMENT HANDLE | REPAIR KIT |
|---------|----------------------------|---------|-----------|--------------|--------|--------------------|------------|
| V050 | 1/2" FULL PORT VALVE | 300 | 1/2" | 3/4" | 24/box | V10153A | V07200 |
| V075 | 3/4" FULL PORT VALVE | 300 | 3/4" | 3/4" | 24/box | V10153A | V07200 |
| V100 | 1" STANDARD PORT VALVE | 225 | 1" | 3/4" | 24/box | V10153A | V07200 |
| V100FP | 1" FULL PORT VALVE | 300 | 1" | 1" | 24/box | V10153A | V10200 |
| V125 | 1 1/4" STANDARD PORT VALVE | 300 | 1 1/4" | 1" | 24/box | V10153A | V10200 |
| V125FP | 1 1/4" FULL PORT VALVE | 225 | 1 1/4" | 1 1/2" | 24/box | V20153 | V20200 |
| V150 | 1 1/2" FULL PORT VALVE | 225 | 1 1/2" | 1 1/2" | 24/box | V20153 | V20200 |
| V200 | 2" STANDARD PORT VALVE | 225 | 2" | 1 1/2" | 24/box | V20153 | V20200 |

FEATURES

- FKM seals.
- Precision molded polypropylene is reinforced with fiberglass for additional strength.
- Self-aligning ball moves freely against the PTFE seats for smooth operation. The valve opens and closes with very little pressure on the handle.
- Ball is diamond turned, after molding, to make it spherically perfect, which provides precise contact between ball and seats.
- PTFE self-lubricating stem bushings and seats cannot stick or bind.
- Stainless steel bolts.

REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring

VALVE ACCESSORIES



V25270

V25271

FEATURES

- 304 stainless steel construction
- Installs under valve handle
- Comes complete with handle and locking device
- Padlock not included

VALVE ACCESSORIES

| PART NO | DESCRIPTION | FITS VALVES | QTY |
|-----------|------------------------------|--------------------|-----|
| VL20153 | LOCKING DEVICE | V125, V150, V200 | 1 |
| V10270 | STRAIGHT MOUNTING BRACKET | V100FP, V125 | 1 |
| V10271 | 90° MOUNTING BRACKET | V100FP, V125 | 1 |
| V25270 | STRAIGHT MOUNTING BRACKET | V125FP, V150, V200 | 1 |
| V25271 | 90° MOUNTING BRACKET | V125FP, V150, V200 | 1 |
| V10153138 | 1" X 1 3/8" HANDLE OFFSET | V100FP, V125 | 1 |
| V20153138 | 2" FP X 1 3/8" HANDLE OFFSET | V125FP, V150, V200 | 1 |
| V25153138 | 2" FP X 1 3/8" HANDLE OFFSET | V200FP | 1 |



2"-4" 6 BOLTED VALVES

FEATURES

- FKM seals.
- Precision molded polypropylene is reinforced with fiberglass for additional strength.
- Self-aligning ball moves freely against the PTFE seats for smooth operation. The valve opens and closes with very little pressure on the handle.
- Ball is diamond turned, after molding, to make it spherically perfect, which provides precise contact between ball and seats.
- PTFE self-lubricating stem bushings and seats cannot stick or bind.
- Stainless steel bolts.

REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring



6 BOLTED VALVES

| PART NO | DESCRIPTION | MAX PSI | PIPE SIZE | OPENING THRU BALL | QTY | REPLACEMENT HANDLE | REPAIR KIT |
|-----------|---------------------------------|---------|-----------|-------------------|-------|--------------------|------------|
| V200FP | 2" FULL PORT VALVE | 225 | 2" | 2" | 8/box | V25153 | V25200 |
| V300 | 3" STANDARD PORT VALVE | 225 | 3" | 2½" | 8/box | V25153 | V30200 |
| V300FP | 3" FULL PORT VALVE | 200 | 3" | 3" | 6/box | V25153 | V35200 |
| V400 | 4" STANDARD PORT VALVE | 100 | 4" | 3½" | 4/box | V25153 | V40200 |
| VFMT200FP | 2" FULL PORT VALVE W/ F ADAPTER | 225 | 2" | 2" | 6/box | V25153 | V25200 |

VALVE ACCESSORIES

FEATURES

- Stainless steel hardware
- Locks in open and closed positions
- Locking handle replaces standard handle (sold separately)
- Padlock not included



VALVE ACCESSORIES

| PART NO | DESCRIPTION | FITS VALVES | QTY |
|---------|---------------------------|--|-----|
| VL25153 | LOCKING HANDLE | V200FP, V300, V300FP, V400, VFMT200FP, VFMT200FPSH | 1 |
| V25270 | STRAIGHT MOUNTING BRACKET | V200FP, V300, V300FP, V400, VFMT200FP, VFMT200FPSH | 1 |
| V25271 | 90° MOUNTING BRACKET | V200FP, V300, V300FP, V400, VFMT200FP, VFMT200FPSH | 1 |



VFMT204FP

V204FP

4 BOLTED FULL PORT VALVES

| PART NO | DESCRIPTION | MAX PSI | PIPE SIZE | OPENING THRU BALL | QTY | REPLACEMENT HANDLE | REPAIR KIT |
|-----------|--|---------|-----------|-------------------|-------|--------------------|------------|
| VFMT204FP | 2" FULL PORT VALVE MALE NPT X MALE ADAPTER | 150 | 2" | 2" | 6/box | V25153 | V25200 |
| V204FP | 2" FULL PORT VALVE | 150 | 2" | 2" | 8/box | V25153 | V25200 |

2" FULL PORT BOLTED BALL VALVES

FEATURES

- FKM seals
- Stainless steel bolts
- PTFE self-lubricating stem bushings and seats cannot stick or bind
- Precision molded in fiberglass reinforced polypropylene
- Self-aligning ball moves freely against the PTFE seats for smoother operation
- Valve opens and closes with very little pressure on the handle
- Ball is diamond turned after molding to make it spherically perfect, which provides precise contact between ball and seats

REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring



VSF200FFAF

VSMT200FFAF

4 BOLTED FULL PORT VALVES

| PART NO | DESCRIPTION | MAX PSI | PIPE SIZE | OPENING THRU BALL | QTY | REPLACEMENT HANDLE | REPAIR KIT |
|-------------|--|---------|-----------|-------------------|-------|--------------------|------------|
| VSF200FFAF | 2" FULL PORT VALVE MALE ADAPTER X 2" ANSI FLANGE | 200 | 2" | 2" | 6/box | V25153SH | VS25200 |
| VSMT200FFAF | 2" FULL PORT VALVE | 200 | 2" | 2" | 6/box | V25153SH | VS25200 |

2" FULL PORT ANSI FLANGE BOLTED BALL VALVES

FEATURES

- 100% PTFE seats
- FKM seals
- Glass-filled polypropylene
- Unique compact design
- Lightweight
- Gaskets featured on page 73

REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring

2" STANDARD PORT STUBBY BALL VALVES

FEATURES

- Stainless steel bolts
- Glass reinforced polypropylene
- Multiple design options
- Unique patented compact design
- Lightweight
- All PTFE seals

REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring



VSF200



VSMT200



VSFMT200



VSFHB200

2" STANDARD PORT STUBBY VALVES

| PART NO | DESCRIPTION | MAX PSI | PIPE SIZE | OPENING THRU BALL | QTY | REPLACEMENT HANDLE | REPAIR KIT |
|----------|---------------------------------|---------|-----------|-------------------|--------|--------------------|------------|
| VSF200 | 2" MALE ADAPTER X 2" FEMALE NPT | 100 | 2" | 1½" | 24/box | VS20152SH | VS20200 |
| VSMT200 | 2" MALE NPT X 2" FEMALE NPT | 100 | 2" | 1½" | 24/box | VS20152SH | VS20200 |
| VSFMT200 | 2" MALE ADAPTER X 2" MALE NPT | 225 | 2" | 1½" | 24/box | VS20152SH | VS20200 |
| VSFHB200 | 2" MALE ADAPTER X 2" HOSE BARB | 100 | 2" | 1½" | 24/box | VS20152SH | VS20200 |

2" FULL PORT STUBBY BALL VALVES



VSMT204FP



VSF204FP



VS204FP



VSFMT204FP



VSFMT204HSFP

FEATURES

- Stainless steel bolts
- 100% PTFE ball seats
- Glass reinforced polypropylene
- Unique patented compact design
- Lightweight
- FKM body seals

REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring

2" STANDARD PORT STUBBY VALVES

| PART NO | DESCRIPTION | MAX PSI | PIPE SIZE | OPENING THRU BALL | QTY | REPLACEMENT HANDLE | REPAIR KIT |
|--------------|--|---------|-----------|-------------------|--------|--------------------|------------|
| VSMT204FP | 2" MALE NPT X 2" FEMALE NPT | 200 | 2" | 2" | 18/BOX | VS25153 | VS25200 |
| VSF204FP | 2" MALE ADAPTER X 2" FEMALE NPT | 100 | 2" | 2" | 18/BOX | VS25153 | VS25200 |
| VS204FP | 2" FEMALE NPT X 2" FEMALE NPT | 225 | 2" | 2" | 18/BOX | VS25153 | VS25200 |
| VSFMT204FP | 2" MALE ADAPTER X 2" MALE NPT | 150 | 2" | 2" | 18/BOX | VS25153 | VS25200 |
| VSFMT204HSFP | 2" FP MALE ADAPTER X 2" MALE NPT W/ SS BALL, STEM & HANDLE | 150 | 2" | 2" | 18/BOX | VS25153SS | VSSH25200 |

3" STANDARD PORT STUBBY BALL VALVES

FEATURES

- Stainless steel bolts
- Glass reinforced polypropylene
- FKM body seals
- Unique patented compact design
- Lightweight
- All PTFE seals

REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring



3" STANDARD PORT STUBBY VALVES

| PART NO | DESCRIPTION | MAX PSI | PIPE SIZE | OPENING THRU BALL | QTY | REPLACEMENT HANDLE STRAIGHT | REPLACEMENT HANDLE SHORT | REPAIR KIT |
|----------|---------------------------------|---------|-----------|-------------------|-------|-----------------------------|--------------------------|------------|
| VSF300 | 3" FEMALE NPT X 3" MALE ADAPTER | 100 | 3" | 2½" | 6/box | V25153 | V25153SH | VS30200 |
| VSMT300 | 3" FEMALE NPT X 3" MALE NPT | 100 | 3" | 2½" | 6/box | V25153 | V25153SH | VS30200 |
| VSFMT300 | 3" MALE NPT X 3" MALE ADAPTER | 225 | 3" | 2½" | 6/box | V25153 | V25153SH | VS30200 |

3" FULL PORT STUBBY BALL VALVES

FEATURES

- Stainless steel bolts
- Glass reinforced polypropylene
- FKM body seals
- Unique patented compact design
- Lightweight
- All PTFE ball seats

REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring



3" FULL PORT STUBBY VALVES

| PART NO | DESCRIPTION | MAX PSI | PIPE SIZE | OPENING THRU BALL | QTY | REPLACEMENT HANDLE | REPAIR KIT |
|--------------|--|---------|-----------|-------------------|-------|--------------------|------------|
| VSFMT300FP | 3" FULL PORT MALE ADAPTER X 3" MALE NPT | 100 | 3" | 3" | 6/box | V25153 | VS35200 |
| VSFMT300HSFP | 3" FULL PORT MALE ADAPTER X 3" MALE NPT W/SS BALL, STEM & HANDLE | 100 | 3" | 3" | 6/box | VS30153SS | VSSH35200 |

3 WAY BOTTOM LOAD BALL VALVES

FEATURES

- Stainless steel bolts
- Precision molded in fiberglass reinforced polypropylene for additional strength
- Self-aligning ball moves freely against the PTFE seats for smooth operation
- Ball is diamond turned after molding to make it spherically perfect, which provides precise contact between ball and seats
- PTFE self-lubricating stem bushings and seats
- FKM body seals
- Directional flow, right or left. Valve can be turned off to stop flow



V100BL

V150BL

V200BL

3 WAY BOTTOM LOAD VALVES

| PART NO | DESCRIPTION | MAX PSI | PIPE SIZE | OPENING THRU BALL | QTY | HANDLE TYPE | REPLACEMENT HANDLE | REPAIR KIT |
|---------|-----------------------------|---------|-----------|-------------------|--------|-------------|--------------------|------------|
| V075BL | ¾" 3-WAY BOTTOM LOAD VALVE | 200 | ¾" | 1" | 18/box | T | V10353TB | V10300SL |
| V100BL | 1" 3-WAY BOTTOM LOAD VALVE | 225 | 1" | 1" | 18/box | T | V10353TB | V10300SL |
| V125BL | 1¼" 3-WAY BOTTOM LOAD VALVE | 300 | 1¼" | 1½" | 12/box | T | V20353TB | V15300SL |
| V150BL | 1½" 3-WAY BOTTOM LOAD VALVE | 225 | 1½" | 1½" | 12/box | T | V20353TB | V15300SL |
| V200BL | 2" 3-WAY BOTTOM LOAD VALVE | 200 | 2" | 2" | 8/box | STRAIGHT | V25353B | V25200BL |

3 WAY SIDE LOAD BALL VALVES

FEATURES

- Stainless steel bolts
- Precision molded in fiberglass reinforced polypropylene for additional strength
- Self-aligning ball moves freely against the PTFE seats for smooth operation
- Ball is diamond turned after molding to make it spherically perfect, which provides precise contact between ball and seats
- PTFE self-lubricating stem bushings and seats
- FKM body seals
- Directional flow, right or left. Valve cannot be turned off to stop flow



V100SL

V150SL

V200SL

3 WAY SIDE LOAD VALVES

| PART NO | DESCRIPTION | MAX PSI | PIPE SIZE | OPENING THRU BALL | QTY | HANDLE TYPE | REPLACEMENT HANDLE | REPAIR KIT |
|---------|---------------------------|---------|-----------|-------------------|--------|-------------|--------------------|------------|
| V075SL | ¾" 3-WAY SIDE LOAD VALVE | 200 | ¾" | 1" | 18/box | STRAIGHT | V10153A | V10300SL |
| V100SL | 1" 3-WAY SIDE LOAD VALVE | 200 | 1" | 1" | 18/box | STRAIGHT | V10153A | V10300SL |
| V125SL | 1¼" 3-WAY SIDE LOAD VALVE | 300 | 1¼" | 1½" | 12/box | T | V20353TS | V15300SL |
| V150SL | 1½" 3-WAY SIDE LOAD VALVE | 225 | 1½" | 1½" | 12/box | T | V20353TS | V15300SL |
| V200SL | 2" 3-WAY SIDE LOAD VALVE | 225 | 2" | 2" | 8/box | STRAIGHT | V25153SH | V25200BL |

VALVES



1½" - 2" NOZZLE VALVES

FEATURES

- Lightweight hose end valve for convenient transfer of liquids into drums, tanks etc
- Angled end flange with 8" long polypropylene fill spout
- All stainless steel bolts

REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring



VA150



VA200FP

1½"-2" NOZZLE VALVES

| PART NO | DESCRIPTION | MAX PSI | PIPE SIZE | OPENING THRU BALL | FEMALE NPT | QTY | REPLACEMENT HANDLE | REPAIR KIT |
|---------|-----------------------------------|---------|-----------|-------------------|------------|--------|--------------------|------------|
| VA150 | 1½" NOZZLE VALVE WITH 90° ELBOW | 225 | 1½" x 8" | 1½" | 1½" | 12/box | V20152 | V20200 |
| VA200 | 2" NOZZLE VALVE WITH 90° ELBOW | 200 | 2" x 8" | 1½" | 2" | 12/box | V20152 | V20200 |
| VA200FP | 2" FP NOZZLE VALVE WITH 90° ELBOW | 225 | 2" x 8" | 2" | 2" | 6/box | V25152 | V25200 |

1" DISPENSING NOZZLES

FEATURES

- Glass reinforced polypropylene
- 304 stainless steel handle, spring and pin
- FKM rubber parts only
- Resists corrosion

REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring



VN100



V10161

1" DISPENSING NOZZLE

| PART NO | DESCRIPTION | MAX PSI | PIPE SIZE | OPENING THRU BALL | FEMALE NPT | QTY | REPLACEMENT HANDLE | REPAIR KIT |
|---------|---|---------|-----------|-------------------|------------|-----|--------------------|------------|
| VN100 | 1" DISPENSING NOZZLE | 150 | 1" | N/A | 1" | 1 | VN10253 | VN10200 |
| V10161 | 1" NOZZLE PIPE FOR USE WITH V100, V100FP, UV100FP, SUV100FP | N/A | 1" | N/A | 1" | 1 | | |



SUV125FP



MSUV100FP

1/2"-2" SINGLE UNION SPINWELD VALVES

| PART NO | DESCRIPTION | MAX PSI | PIPE SIZE | OPENING THRU BALL | QTY |
|-----------|---|---------|-----------|-------------------|-----|
| SUV050FP | 1/2" FULL PORT SINGLE UNION SPINWELD VALVE | 300 | 1/2" | 1/2" | 1 |
| SUV075FP | 3/4" FULL PORT SINGLE UNION SPINWELD VALVE | 300 | 3/4" | 3/4" | 1 |
| SUV100FP | 1" FULL PORT SINGLE UNION SPINWELD VALVE | 300 | 1" | 1" | 1 |
| SUV125FP | 1 1/4" FULL PORT SINGLE UNION SPINWELD VALVE | 300 | 1 1/4" | 1 1/4" | 1 |
| SUV150FP | 1 1/2" FULL PORT SINGLE UNION SPINWELD VALVE | 300 | 1 1/2" | 1 1/2" | 1 |
| SUV200FP | 2" FULL PORT SINGLE UNION SPINWELD VALVE | 200 | 2" | 2" | 1 |
| MSUV100FP | 1" MANIFOLD FULL PORT SINGLE UNION SPINWELD VALVE | 300 | | 1" | 1 |

1/2" - 2" SINGLE UNION SPINWELD VALVES

FEATURES

- Precision molded in glass reinforced polypropylene for strength and chemical resistance
- PTFE seats for smooth and proper sealing characteristics
- EPDM O-rings to handle most fertilizers and many chemicals
- Double O-rings in stem area for extra sealing protection
- Interlocking body and end plate to allow easy thread connection when installing valves



1/2"-2" SINGLE UNION VALVES

| PART NO | DESCRIPTION | MAX PSI | PIPE SIZE | OPENING THRU BALL | QTY |
|---------|-------------------------------------|---------|-----------|-------------------|-----|
| UV050FP | 1/2" FULL PORT SINGLE UNION VALVE | 300 | 1/2" | 3/4" | 1 |
| UV075FP | 3/4" FULL PORT SINGLE UNION VALVE | 300 | 3/4" | 3/4" | 1 |
| UV100FP | 1" FULL PORT SINGLE UNION VALVE | 300 | 1" | 1" | 1 |
| UV125FP | 1 1/4" FULL PORT SINGLE UNION VALVE | 225 | 1 1/4" | 1 1/4" | 1 |
| UV150FP | 1 1/2" FULL PORT SINGLE UNION VALVE | 200 | 1 1/2" | 1 1/2" | 1 |
| UV200FP | 2" FULL PORT SINGLE UNION VALVE | 300 | 2" | 2" | 1 |

1/2" - 2" SINGLE UNION VALVES

FEATURES

- Precision molded in glass reinforced polypropylene for strength and chemical resistance
- PTFE seats for smooth and proper sealing characteristics
- Double O-rings in stem area for extra sealing protection
- Interlocking body and end plate to allow easy thread connection when installing valves