

## Quiet, compact power!

## **PSS8B4W**Packaged Standby Generator

## **FEATURES**

- · Easily installed outside new or existing homes
- Critical grade exhaust system for quieter operation
- Low maintenance Emissions compliant
- Sound attenuated housing constructed of galvannealed steel with durable powder paint finish
- Direct natural gas or LP fuel system
- Requires 4-Wire ULATS165 transfer switch for automatic operation (sold separately - see specs below)



		POWER RATING-CONTINUOUS STANDBY (1)						
MODEL	POWER	L.P. Gas		N	Natural Gas			
NUMBER	OUTPUT (60hz)	KW	KVA	<b>AMPS</b>	KW	KVA	<b>AMPS</b>	
PSS8B4W	120/240V, 1-Phase, 1.0 p.f.	8.0	8.0	33	7.2	7.2	30	

	, , , , , , ,						
Engine Specifications		Generator Data					
Make/Model	B&S Vanguard	Generator Type (4)	RFL				
Displacement	480 c.c.	Voltage Regulation	+/- 5%				
Rated Power (1)	16 hp	Frequency Regulation	+/- 3%				
Engine Speed	3600 rpm	Motor Starting Ability (5)	4 hp				
Engine Features		Size and Weight					
Electronic Ignition	Standard	L x W x H (in)	30.5 x 27.3 x 27.4				
Cooling System	Air	Ship Weight (lbs)	365				
Vapor Fuel System	Standard	Warranty Information					
Critical Grade Exhaust System	Standard	Engine/Generator	2 Years/1 Year				
DBA Rating @ 7 meters (23 ft) 68 N-L/70 F-L Battery Rack/Cables (3) Standard		Optional Accessories  2-Wire Controller for 2-Wire Start Systems					
Control System		Vapor Fuel Filter					
Auto-Off-Test Switch	Standard	Battery Heater					
Low Oil Protection	Standard	ULATS165 Auto Transfer Switch (sold separately)					
Float Battery Charger	Standard	Engine Start Delay	3 Seconds				
Running Time Meter	Standard	Cycle Cranking	Standard				
Fuel Consumption		Overcrank Limiting	Standard				
Full Load - LP Gas (2)	1.60 gal/hr	Transfer Delay	15 Seconds				
Half Load - LP Gas (2)	1.00 gal/hr	Retransfer Delay	5 Minutes				
Full Load - Natural Gas	132 ft <sup>3</sup> /hr	Engine Cooldown Delay	1 Minute				
Half Load - Natural Gas	95 ft <sup>3</sup> /hr	14-Day Exercise Circuit	Standard				
Required Fuel Pressure	4-6 oz or 7-11" w.c.	Warranty	1 Year				

## NOTES:

- (1) Derate 3.5% per 1,000 feet elevation above sea level
- (2) One gallon of L.P. gas equals 4.23 lbs
- (3) Battery not included. Requires 12-volt Group U1, 235 cca battery
- (4) Rotating Field Brushless design generator
- (5) Code G capacitor start motor



225 South Cordova Ave Le Center MN 56057 East Coast: (800) 733-2112

West Coast & Canada: (800) 324-8174 E-Mail: wincosales@wincogen.com Web Site: www.wincogen.com