

WCL Series

The WCL Series offers the following features:

- The choice between a 300-gallon or 600-gallon cone-shaped tank for effective settling and easy handling of heavy solids
- Solids separation chamber with bag filter and decanting
- Oil skimmer and decanter for easy handling of oil
- CSA approved control panel meets the requirements of the US and Canadian standards for an Industrial Control Panel
- 1.0 HP surface-mount sump pump



WCL-30D-0M10

MODEL NUMBER	FLOW RATE	CLARIFIER TANK	OIL COALESCING AREA	POWER REQUIREMENTS	DIMENSIONS (LxWxH)	SHIP WT.
WCL-10S-0M10**	0-10 GPM	300 gallons	48 sq. ft.	230V, 1Ø, 8.0A	48x67x97in.	641 lb.
WCL-30S-0M10**	0-30 GPM	600 gallons	73 sq. ft.	230V, 1Ø, 8.0A	63x75x106in.	725 lb.
WCL-30D-0M10^	0-30 GPM	600 gallons	425 sq. ft.	230V, 1Ø, 13.0A	63x75x106in.	980 lb.

*Float consists of 230V plug.

+Control panel not included.

^Ozone is included.

Surface-mount sump pump included on all models.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
855-0015	Treated-water storage tank - 80-gallons, for transferring water to the next process or point of discharge	All models
855-0016	Treated-water storage tank - 165-gallons, for transferring water to the next process or point of discharge	All models
RC-0005-0001	Mezzanine stand - For convenient access to the oil skimmer and to the top portion of the tank	WCL-30 models