


## SX17



<b>WIRING DIAGRAMS</b>	<ul style="list-style-type: none"> <li>▶ Neon or fluorescent lamp</li> <li>▶ Anti-luminiscence resistor available</li> <li>▶ LED in A.C. or D.C. version</li> </ul>
<b>VOLTAGE</b>	2V, 12V, 24V, 125V, 250V, 400V
<b>TEMPERATURE</b>	From T75 °C to T150 °C according to the version
<b>COLOUR</b>	Red, orange, green, blue, colourless. Other colours available on customer's request
<b>WIRE ENDS AND CONNECTORS</b>	PVC or silicone cables, available pre-stripped wires end 6,5 mm or with clamped connectors
<b>LIGHT SOURCE</b>	LED: available for every voltage Incandescence: 12V - 24V Neon: from 125V



## SX21 / SX214

<b>WIRING DIAGRAMS</b>	<ul style="list-style-type: none"> <li>▶ Neon or fluorescent lamp</li> <li>▶ Anti-luminiscence resistor available</li> <li>▶ LED in A.C. or D.C. version</li> </ul>
<b>VOLTAGE</b>	2V, 12V, 24V, 125V, 250V, 400V
<b>TEMPERATURE</b>	From T75 °C to T150 °C according to the version
<b>COLOUR</b>	Red, orange, green, blue, colourless. Other colours available on customer's request
<b>WIRE ENDS AND CONNECTORS</b>	PVC or silicone cables, available pre-stripped wires end 6,5 mm or with clamped connectors
<b>LIGHT SOURCE</b>	LED: available for every voltage Incandescence: 12V - 24V Neon: from 125V

15

**LENS 57**


HOLE Ø 10 mm

**LENS 41**


HOLE Ø 12 mm

**LENS 51**


HOLE Ø 12 mm

**LENS 43**


HOLE Ø 13 mm

**LENS 53**


HOLE Ø 13 mm

**LENS 59**


HOLE Ø 13 mm

## SX21T Lenses


**LENS P**


HOLE Ø 11,5 mm

**LENS Q**


HOLE 10,5x7 mm

## SX214 Lenses



HOLE Ø 6 mm

## SX24 / SX244

<b>WIRING DIAGRAMS</b>	<ul style="list-style-type: none"> <li>▶ Neon or fluorescent lamp</li> <li>▶ Anti-luminiscence resistor available</li> <li>▶ LED in A.C. or D.C. version</li> </ul>
<b>VOLTAGE</b>	2V, 12V, 24V, 125V, 250V, 400V
<b>TEMPERATURE</b>	From T75 °C to T150 °C according to the version
<b>COLOUR</b>	Red, orange, green, blue, colourless. Other colours available on customer's request
<b>WIRE ENDS AND CONNECTORS</b>	PVC or silicone cables, available pre-stripped wires end 6,5 mm or with clamped connectors
<b>LIGHT SOURCE</b>	LED: available for every voltage Incandescence: 12V - 24V Neon: from 125V