



FLEETCLEAN SYSTEMS LLC

401.356.4156
www.fleetcleansystems.com
sales@fleetcleansystems.com

Specifications

ATTRIBUTE	DESCRIPTION
Physical Form	Brown Liquid
Odor	Mild Caustic Odor
Solubility	Complete in Water
Foam	Moderate
Viscosity	Water like
pH (Typical)	11
Flash Point	Not Applicable

Dilution Ratios

Use	Dilution
Heavy	5:1 - 10:1
Moderate	10:1 - 15:1
Light	15:1 - 25:1

Available In

PART #	SIZE
02B130	5 Gal.
02B131	55 Gal.
02B132	275 Gal.



FCS #2B NEUTRALIZER

Tech Data Sheet

Aggressive truck wash that is excellent in removing road film, diesel smoke, and grease. Excellent for painted surfaces. Can be used as a 1 step, but most effective as part of 2 Step wash process. Do not use on anodized or mirror polished aluminum

Benefits

- ◆ Safe on painted surfaces
- ◆ Helps remove difficult grease and oils without brushing
- ◆ Environmentally friendly, resulting in a nearly NEUTRAL WASTE water when paired with 1 Step detergents. There is less need for waste disposal solvents or high phosphates.

Applications

- ◆ Brightens and whitens non-polished aluminum
- ◆ Use as a 2nd Step fleet brushless fleet cleaning.
- ◆ Neutralizes acidic pre-soak detergents guarding against new film buildup.

Precautions

- ◆ DO NOT ALLOW TO DRY ON ANY SURFACE
- ◆ DO NOT USE ON POLISHED OR ANODIZED ALUMINUM
- ◆ CONTAINS SODIUM HYDROXIDE. PERSONAL PROTECTION EQUIPMENT SHOULD BE WORN

Note: Cleaning effectiveness is affected by: temperature, concentration, dwell time, water hardness, and soap application pressure. Soap concentration may be adjusted to compensate for changes in these conditions.