

WAGGOTT CAMS

No.	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
			Advertised		@.050"		Cam		Valve		@T.D.C.						
	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
215	32-75	76-31	287	287	243	240	.292	.292	.423	.420	.075	.073	.015	.018	113	111	
104	47-78	80-48	305	308	251	254	.325	.330	.468	.473	.104	.104	.020	.022	105	108	
250	40-84	86-44	304	310	255	259	.325	.330	.468	.473	.109	.109	.020	.022	107	109	
467	34-63	73-32	277	285	249	258	.360	.365	.514	.522	.113	.092	.026	.026	106	110	
164	38-85	90-38	303	308	253	251	.320	.320	.455	.455	.078	.072	.025	.025	113	114	
120	47-90	83-47	317	310	265	264	.355	.350	.511	.503	.105	.095	.022	.022	110	109	
178	46-81	84-45	307	309	264	265	.350	.350	.505	.503	.105	.090	.020	.022	107	109	

CODE: CHEV 350 SOLID
 PERFORMANCE - 48G
 STANDARD - 48S
 BILLET - EP1
 EXCHANGE - DEP 350

NOTES: SOLID CAM FOLLOWERS PT#AT992
 DOUBLE OR TRIPLE SPRINGS ARE REQUIRED

350 SOLID

ROCKER RATIO 1.5

CHEV