## **DEALER HOT WATER PRESSURE WASHERS**

### **Skid Gasoline**

**Belt Drive I HDC Series** 

This hot water belt drive skid is one of the most efficient and cost effective pressure washers you can buy. The heavy-duty frame means you can take it to any jobsite and it will hold up to the demands of the job.





### Pump

- Belt drive triplex piston AR or General pump with ceramic plungers
- Adjustable high pressure detergent injector

#### Engine

- Performance-proven industrial gasoline engine with electric start – battery not included

### Frame

- Heavy-duty powder coated steel square tube skid frame
- Stainless-steel coil wrap prevents rusting

### Components

- Stainless-steel wrap heat exchanger with ½-inch schedule 80 pipe coil
- Polyethylene engine and burner fuel tanks
- 12V Beckett burner no need for a generator battery not included
- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)
- Large polyethylene float tank

#### Miscellaneous

 Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

#### **Unit Includes:**

- Quick connect nozzles 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch steel wire-braided high pressure hose
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off



Made in

**Exclusive** 

Dealer

**Product** 

# **DEALER HOT WATER PRESSURE WASHERS**

# **Skid Gasoline**

## **Belt Drive I HDC Series**



Model Number	PSI	GPM	Displacement/Engine	Pump	Engine Fuel Tank Capacity	Burner Fuel Tank Capacity	Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HDC-3005-0K6G	3000	4.8	624cc Kohler CH620 OHV	General	10.0 gallons	10.0 gallons	2.76 gph	386,400	50x34x46in.	844 lb.	725 lb.
HDC-3005-0V6G	3000	4.8	480cc Vanguard OHV	General	10.0 gallons	10.0 gallons	2.76 gph	386,400	50x34x46in.	844 lb.	725 lb.
HDC-3505-1H6G	3500	4.7	GX630 Honda OHV	General	10.0 gallons	10.0 gallons	2.76 gph	386,400	50x34x46in.	844 lb.	725 lb.
HDC-3505-0K6G*	3500	4.7	624cc Kohler CH620 OHV	General	10.0 gallons	10.0 gallons	2.76 gph	386,400	50x34x46in.	844 lb.	725 lb.
HDC-4004-1H6A	4000	4.0	GX630 Honda OHV	AR	10.0 gallons	10.0 gallons	2.45 gph	343,000	50x34x46in.	844 lb.	725 lb.

<sup>\*</sup>Higher performance 624cc Kohler engine.

Options:					
Part Number	Description	Fits Models			
HX-0130	Three-way ball valve - Allows the pressure washer to be operated from garden hose, float tank or trailer supply by adjusting ball level valve	All models			
HX-0147	Four-point lifting capability - Allows unit to be lifted by a crane	All models			
HX-0156	Hour meter - Displays the number of hours unit has been in operation	All models			
HX-0200	Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas	HDC-3005 & HDC-3505 models			
HX-0212	Adjustable temperature control - Operator is able to adjust outlet water temperature between 96°F-250°F	All models			
HX-0229	Clutch drive pump - Stops the pump from spinning in bypass mode and helps to extend the life of the pump, changes GPM to 4.3 when added to the unit	3000-PSI models			
HX-0230	Clutch drive pump - Stops the pump from spinning in bypass mode and helps to extend the life of the pump, changes GPM to 4.2 when added to the unit	3500-PSI models			
HX-0266	Clutch drive pump - Stops the pump from spinning in bypass mode and helps to extend the life of the pump, standard flow rate	HDC-3005 & HDC-3505 models			

Accessories:					
Part Number	Description	Fits Models			
50-0170	Stack adapter - Allows 8-inch flue pipe to be installed to boiler exhaust port	All models			
850-0324	Gasket (For 50-0170) - Seals between 50-0170 stack adapter and boiler housing	All models			
AW-5740-0000	Wheel kit - Allows unit to become portable	All models			
AW-6000-1006	· · · · · · · · · · · · · · · · · · ·	All models			
	drawstrings to secure cover, Mi-T-M logo				
AW-6000-1007	· · · · · · · · · · · · · · · · · · ·	All models			
	drawstrings to secure cover, no logo				

POWERED by HONDA