

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
448	STD	16-50	55-14	245	248	189	189	.240	.240			.023	.020	HYD	HYD	108	110	3Y - 4Y
113	STD	22-60	58-19	260	260	189	189	.237	.237			.022	.020	HYD	HYD	100	115	3Y EFI
207	STD	10-43	45-8	232	232	177	177	.225	.225			.015	.011	HYD	HYD	106	108	2Y
229	1	23-56	62-21	259	263	196	196	.242	.243			.028	.022	HYD	HYD	106	112	TORQUE - 2Y
656	1	16-55	67-15	252	257	195	202	.268	.0260			.023	.020	HYD	HYD	110	112	TORQUE - 3Y - 4Y
403	1	21-60	63-19	260	262	201	202	.272	.272			.032	.028	HYD	HYD	108	111	

CODE: TOYOTA 3Y
 PERFORMANCE - 44G
 STANDARD - 44S
 BILLET - EP288
 EXCHANGE - DEP 3Y
 FOLLOWERS -RHT 969

NOTES: DIST GEAR CAN WEAR BADLY. SO ASK

2Y- 3Y- 4Y

TOYOTA