



8 / 12 channels

12 channels

& option input card 4 channels



## SE-2800 DATAVIDEO

Supports 8 or 12 HD or SD Inputs in a variety of configurations:

### HD Mode

- 1) 8 / 12 HD-SDI
- 2) 6 / 9 HD-SDI + 2 / 3 HDMI

### SD Mode

- 1) 8 / 12 SD-SDI
- 2) 4 / 6 SD-SDI + 4 / 6 composite video (CVBS)
- 3) 4 / 6 SDI + 2 / 3 HDMI + 2 / 3 CVBS

3 SDI Outputs assignable to AUX, Program (PGM), Preview (PVW) or PGM clean - Built-in SD down-scaler on CH-3 SDI output

2 HDMI outputs for multiview monitoring

**AUDIO Input:** 4 analogue balanced XLR

**AUDIO Output:** 2 analogue balanced XLR. Supports embedded audio SDI output from 4-CH XLR Audio input

Two DSK, supports Key and Fill

Cut, Mix and Wipe with borders

Clock on screen

Countdown counter on multiscreen

Two PIP displays with user-defined borders

Tally, GPI interface and RJ45 for firmware upgrade

Audio Delay up to 16 fields, or 8 frames

DC 12V operation voltage, available for mobile use

[info@mediamat.be](mailto:info@mediamat.be)