



30-Gallon

Air Compressors

Two Stage – Diesel



ABS-9KD-30H

Compressor Pump:

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

Engine:

- Electric start - battery, box and cables not included
- Glow plug equipped engine for easy starting in cold temperatures

Frame:

- Powder coated ASME coded 30-gallon receiver tank
- 3/8-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard
- Removable base plate offers flexible installation

Components:

- Regulator and two gauges for tank and outlet pressure
- ASME safety valves
- Tank drain valve

Limited Warranties:

- 2 year pump exchange (see page 71 for more information)
- 3 year Kohler engine

Certification:

- ASME Boiler and Pressure Vessel Code - UM

This diesel-powered machine supplies consistent air flow required for commercial and industrial applications. It is designed for optimum performance and productivity and features a large-capacity ASME coded tank.

MODEL NUMBER	CFM @ PSI*	HORSEPOWER/ENGINE	COMPRESSOR	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
ABS-9KD-30H	29.0 @ 175	9.1 HP Kohler KD440 OHV	Two stage, cast iron	Cable throttle	38x23x46.5in.	540 lb.	483 lb.

*Equipped with 150-PSI maximum rated regulator.

Accessory & Option:

PART NUMBER	DESCRIPTION	FITS MODEL
AW-6000-1002	Equipment cover	ABS-9KD-30H
IX-0001	Vibration isolator pads - Isolators protect the unit from vibration during use; Recommended for models that are mounted in service truck applications	ABS-9KD-30H