



1-855-358-7825 www.atp4you.net





## **ATP TG529**

- The drive axle radial optimized for highway and urban road service.
- The superior drive tire for long distance highway and regional use.
- On/Off Road Mixed road and Mining.
- Excellent wet and dry manoeuvrability.
- Minimum wear and long original tread life.
- Good resistance to irregular wear and resists heat generation in casing.
- Wide base and deep grove.
- Deep block tread.

SIZE	RIM	PLY RATING	SPEED	TIRE DIM		LOAD INDEX		INFLATION PRESSURE SINGLE/DUAL		LOAD CAPACITY SINGLE/DUAL	
			SYMBOL	SECTION WIDTH	OVERALL DIAMETER	SINGLE	DUAL	KPA	PSI	KG	LBS
11R22.5	8.25	14	М	1065	279	144	142	720	105	2800 / 2575	6175 / 5675
		16	М			146	143	830	120	3000 / 2725	6610 / 6005
11R24.5	8.25	14	М	1116	279	146	143	720	105	3000 / 2725	6610 / 6005
		16	М			149	146	830	120	3250 / 3000	7160 / 6610
285/ 75R24.5	8.25	14	L/M	1056	283	144	141	760	110	2800 / 2575	6175 / 5675
		16	L/M			146	143	830	120	3000 / 2725	6610 / 6005
295/ 75R22.5	9.00	14	L/M	1020	298	144	141	760	110	2800 / 2575	6175 / 5675
		16	L/M			146	143	830	120	3000 / 2725	6610 / 6005

Warehouse locations: Los Angeles, Phoenix, Tucson, Grand Prairie, Seattle, Boise