



Model Shown:
GEN-6000-OMMO

ChoreMaster® Series Gasoline 3600, 6000 & 8000-Watt

Featuring 3600, 6000 and 8000 watt generators, the ChoreMaster Series come with a Mi-T-M OHV engine and are designed to provide maximum power for contractors and electrical back-up for power outages.

Alternator:

- Total harmonic distortion (THD) less than 6%
- Copper and aluminum windings

Frame:

- Low profile, compact design
- Powder coated wraparound frame with 1-inch steel tubing

Components:

- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Large low tone mufflers
- Engine on/off switch
- Fuel shut-off valve
- DC/battery charging


Certification:

- CSA Certified

Limited Warranties:

- 1 year alternator
- 1 year Mi-T-M engine

USAGE	Commercial	Commercial	Commercial
MODEL NO.	GEN-3600-OMMO	GEN-6000-OMMO	GEN-8000-OMME
MAX. AC OUTPUT	3600 watts	6000 watts	8000 watts
RATED AC OUTPUT	3000 watts	5500 watts	7000 watts
DISPLACEMENT/ENGINE	212cc Mi-T-M OHV	389cc Mi-T-M OHV	420cc Mi-T-M OHV with electric start - battery included
ALTERNATOR	Brushed 120V, 60Hz	Brushed 120V/240V, 60Hz	Brushed 120V/240V, 60Hz
MAX. AMPS (120V/240V)	30.0	50.0/25.0	66.6/33.3
CONT. AMPS (120V/240V)	25.0	45.8/22.9	58.3/29.2
RECEPTACLES	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock	(2) 120V, 20A GFCI duplex; (1) 120V, 30A twist lock; (1) 120V/240V, 30A twist lock	(2) 120V, 20A GFCI duplex; (1) 120V, 30A twist lock; (1) 120V/240V, 30A twist lock
CIRCUIT BREAKERS	(1) Main circuit breaker; (2) 20A circuit breakers, single pole; (1) 10A DC breaker	(1) Main circuit breaker; (2) 20A circuit breakers, single pole; (1) 10A DC breaker	(1) Main circuit breaker; (2) 20A circuit breakers, single pole; (1) 10A DC breaker
RATED SPEED	3600 RPM	3600 RPM	3600 RPM
DECIBEL RATING	72.0	74.0	74.0
FUEL CAPACITY	4.0 gallons	6.6 gallons	6.6 gallons
RUN TIME (AT FULL LOAD)	8.5 hours	6.5 hours	6.0 hours
IDLE CONTROL	No	Yes	Yes
WHEEL KIT	No	Yes, includes tires and rubber gripped handles	Yes, includes tires and rubber gripped handles
DIMENSIONS (LxWxH)	24.9x17.6x17.9in.	39.1x28.7x30.6in.*	39.1x28.7x30.6in.*
SHIP WT.	134 lb.	228 lb.	237 lb.
NET WT.	102 lb.	180 lb.	195 lb.



GFCI 5-20R
All Models



NEMA L5-30R
120VAC
All Models



NEMA L14-30R
120V/240V
GEN-6000 &
GEN-8000 Models

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

*Dimensions include the wheel kit with the handles in the down position.

Consult factory for more information on these available accessories:

- RV generator adapter
- Lifting hook
- Equipment cover

Fleetclean Systems LLC . 1 Tupperware Dr. Ste. 3 North Smithfield RI 02896 . (401) 356-4156 . www.fleetcleansystems.com