

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
638	STD	24-75	55-28	279	263	182	176	.230	.230	.383	.379	.022	.028	.008	.012	111	106	
339	1	18-58	70-30	249	280	184	194	.230	.248	.381	.410	.028	.052	.010	.012	109	110	
666	2	25-64	70-30	269	282	201	202	.263	.264	.437	.437	.038	.032	.010	.012			
645	3	25-66	74-32	275	286	198	220	.245	.253	.408	.420	.055	.078	.008	.010	110	110	
385	3	36-79	77-32	292	289	229	227	.240	.245	.400	.404	.0125	.120	.008	.012	107	109	
198	4	38-78	80-38	296	298	226	236	.280	.280	.466	.464			.010	.012			
728	5			321	332	239	241	.257	.250	.433	.419			.004	.006	108	108	
573		38-79	39-80	294	293	234	236	.330	.330	.551	.549			.010	.012	108	109	
575		46-83	90-53	309	323	247	248	.335	.342	.559	.569	.085	.080	.010	.012	108	109	

CODE: HOLDEN GEMINI
 PERFORMANCE - 44GOHC
 STANDARD - 44SOHC
 BILLET - EP78
 EXCHANGE - DEP GEM

NOTES: VALVES SPRINGS SHOULD BE CHECKED OR REPLACED
 CHECKING &/OR RECURVING OF DISTRIBUTOR IS RECOMMENDED.
 2 TYPES OF HEADS. BEST HAS LARGER THROAT UNDER INLET
 VALVE SEAT.

ROCKER RATIO 1.7

GEMINI

HOLDEN