



1-855-358-7825
www.atp4you.net

ATP NF03+

- Premium five-rib tread provides outstanding handling for steer application
- Decoupling grooves prevent uneven tread wear and ensure long tread life for long distance travelling
- Wide and deep tread guarantee longer mileage with affordable cost and remarkable value



SIZE	RIM	PLY RATING	SPEED SYMBOL	TIRE DIMENSION (mm)		LOAD INDEX		INFLATION PRESSURE SINGLE/DUAL		LOAD CAPACITY SINGLE/DUAL	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE	DUAL	KPA	PSI	KG	LBS
315/80R22.5	9.0	18	L	312	1082	144	142	830	120	3750 / 3450	8270 / 7610
		20	L			146	143	850	125	4000 / 3650	8820 / 8045
12R22.5	9.0	16	L	300	1096	146	143	830	120	3350 / 3075	7390 / 6780
		18	L			149	146	930	135	3550 / 3250	7830 / 7170
295/80R22.5	9.0	18	L	298	1050	144	141	900	130	3550 / 3250	7830 / 7170

Warehouse locations: Los Angeles, Phoenix, Tucson, Grand Prairie, Seattle, Boise



1-855-358-7825
www.atp4you.net

ATP NF25

- Mixed highway, all position heavy duty rib tire for on//off highway application
- Special tread compound designed for lower heating up, excellent puncture and cut resistance and minimized gasoline consumption
- Super steel belt carcass construction enhances casing strength and maximizes tire load capacity



SIZE	RIM	PLY RATING	SPEED SYMBOL	TIRE DIMENSION (mm)		LOAD INDEX		INFLATION PRESSURE SINGLE/DUAL		LOAD CAPACITY SINGLE/DUAL	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE	DUAL	KPA	PSI	KG	LBS
11R22.5	8.25	14	M	1054	279	144	142	720	105	2800 / 2650	6175 / 5675
		16	M			146	143	830	120	3000 / 2725	6610 / 6005
11R24.5	8.25	14	L	1104	279	146	143	720	105	3000 / 2725	6610 / 6005
		16	L			149	146	720	105	3250 / 3000	7160 / 6610
285/75R24.5	9.00	14	L	1050	283	144	141	760	110	2800 / 2575	6175 / 5675
		16	L			147	144	830	120	3000 / 2725	6610 / 6005
295/75R22.5	8.25	14	L	1014	298	144	141	760	110	2800 / 2575	6175 / 5675
		16	L			146	143	830	120	3000 / 2725	6610 / 6005

Warehouse locations: Los Angeles, Phoenix, Tucson, Grand Prairie, Seattle, Boise