




1-855-358-7825
www.atp4you.net

ATP ND20

- Mixed pattern with excellent ground grasping and braking performance
- Low-heating, excellent abrasion resistance and energy-efficient
- Applicable to the driving wheels of the truck



SIZE	RIM	PLY RATING	SPEED SYMBOL	TIRE DIMENSION (mm)		LOAD INDEX		INFLATION PRESSURE SINGLE/DUAL		LOAD CAPACITY SINGLE/DUAL	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE	DUAL	KPA	PSI	KG	LBS
11R22.5	8.25	14	M	1065	279	144	142	720	105	2800 / 2575	6175 / 5675
		16	M			146	143	830	120	3000 / 2725	6610 / 6005
11R24.5	8.25	14	M	1116	279	146	143	720	105	3000 / 2725	6610 / 6005
		16	M			149	146	830	120	3250 / 3000	7160 / 6610
285/75R24.5	8.25	14	L	1056	283	144	141	760	110	2800 / 2575	6175 / 5675
		16	L			146	143	830	120	3000 / 2725	6610 / 6005
295/75R22.5	9.00	14	L	1020	298	144	141	760	110	2800 / 2575	6175 / 5675
		16	L			146	143	830	120	3000 / 2725	6610 / 6005

Warehouse locations: Los Angeles, Phoenix, Tucson, Grand Prairie, Seattle, Boise