



## TRANSPORTATION KING



**1-855-358-7825**  
[www.atp4you.net](http://www.atp4you.net)



## ATP TG519

- The drive axle radial designed for improved or mixed on/off road service.
- Provide excellent traction and off-road performance throughout the life of the tire.
- Effectively improve the self-cleaning performance.
- Provide long tread life.
- Give excellent stability and handling.
- Deep grooves.
- Strong solid shoulders.
- Tough blocks.
- Special pattern design.

SIZE	RIM	PLY RATING	SPEED SYMBOL	TIRE DIMENSION (mm)		LOAD INDEX		INFLATION PRESSURE SINGLE/DUAL		LOAD CAPACITY SINGLE/DUAL	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE	DUAL	KPA	PSI	KG	LBS
11R22.5	8.25	14	M	1065	279	144	142	720	105	2800 / 2575	6175 / 5675
		16	M			146	143	830	120	3000 / 2725	6610 / 6005
11R24.5	8.25	14	M	1116	279	146	143	720	105	3000 / 2725	6610 / 6005
		16	M			149	146	830	120	3250 / 3000	7160 / 6610
285/75R24.5	8.25	14	L/M	1056	283	144	141	760	110	2800 / 2575	6175 / 5675
		16	L/M			146	143	830	120	3000 / 2725	6610 / 6005
295/75R22.5	9.00	14	L/M	1020	298	144	141	760	110	2800 / 2575	6175 / 5675
		16	L/M			146	143	830	120	3000 / 2725	6610 / 6005

**Warehouse locations: Los Angeles, Phoenix, Tucson, Grand Prairie, Seattle, Boise**



# TRANSPORTATION KING



**1-855-358-7825**  
**www.atp4you.net**



# ATP TG529

- The drive axle radial optimized for highway and urban road service.
- The superior drive tire for long distance highway and regional use.
- On/Off Road Mixed road and Mining.
- Excellent wet and dry manoeuvrability.
- Minimum wear and long original tread life.
- Good resistance to irregular wear and resists heat generation in casing.
- Wide base and deep groove.
- Deep block tread.

SIZE	RIM	PLY RATING	SPEED SYMBOL	TIRE DIMENSION (mm)		LOAD INDEX		INFLATION PRESSURE SINGLE/DUAL		LOAD CAPACITY SINGLE/DUAL	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE	DUAL	KPA	PSI	KG	LBS
11R22.5	8.25	14	M	1065	279	144	142	720	105	2800 / 2575	6175 / 5675
		16	M			146	143	830	120	3000 / 2725	6610 / 6005
11R24.5	8.25	14	M	1116	279	146	143	720	105	3000 / 2725	6610 / 6005
		16	M			149	146	830	120	3250 / 3000	7160 / 6610
285/75R24.5	8.25	14	L/M	1056	283	144	141	760	110	2800 / 2575	6175 / 5675
		16	L/M			146	143	830	120	3000 / 2725	6610 / 6005
295/75R22.5	9.00	14	L/M	1020	298	144	141	760	110	2800 / 2575	6175 / 5675
		16	L/M			146	143	830	120	3000 / 2725	6610 / 6005

**Warehouse locations: Los Angeles, Phoenix, Tucson, Grand Prairie, Seattle, Boise**





## TRANSPORTATION KING



**1-855-358-7825**  
**www.atp4you.net**



## ATP TG766

- The all-position radial designed for highway and regional service with superb performance and handling.
- Enhance traction and tread wear.
- Enhance wet traction.
- Enhance dry traction.
- Helps to offer ride comfort.
- Helps to produce low heat, toughness, and reduces squirm for superb handling.
- Enhances fuel economy.
- Circumferential grooves.
- High-tech belt system.
- Fuel-efficient casing.

SIZE	RIM	PLY RATING	SPEED SYMBOL	TIRE DIMENSION (mm)		LOAD INDEX		INFLATION PRESSURE SINGLE/DUAL		LOAD CAPACITY SINGLE/DUAL	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE	DUAL	KPA	PSI	KG	LBS
11R22.5	8.25	14	M	1065	279	144	142	720	105	2800 / 2575	6175 / 5675
		16	M			146	143	830	120	3000 / 2725	6610 / 6005
11R24.5	8.25	14	M	1116	279	146	143	720	105	3000 / 2725	6610 / 6005
		16	M			149	146	830	120	3250 / 3000	7160 / 6610
285/75R24.5	8.25	14	L/M	1056	283	144	141	760	110	2800 / 2575	6175 / 5675
		16	L/M			146	143	830	120	3000 / 2725	6610 / 6005
295/75R22.5	9.00	14	L/M	1020	298	144	141	760	110	2800 / 2575	6175 / 5675
		16	L/M			146	143	830	120	3000 / 2725	6610 / 6005
315/80R22.5	9.0	20	L	312	1076	156	153	850		4000 / 3650	

**Warehouse locations: Los Angeles, Phoenix, Tucson, Grand Prairie, Seattle, Boise**



## TRANSPORTATION KING



**1-855-358-7825**  
**www.atp4you.net**



## ATP TG866

- The all-position radial optimized for highway, on/off road and urban road service.
- Helps to enable lower heating wear resistance and fuel economy benefits. Extended road mileage.
- Helps to ensure excellent high speed and durability.
- Helps to resist stone retention and drilling.
- Helps water draining wet skid resistance and soft soil mobility.
- Ultra-high tire bead structure.
- Zigzag grooves angle.
- Lateral block shoulder.

SIZE	RIM	PLY RATING	SPEED SYMBOL	TIRE DIMENSION (mm)		LOAD INDEX		INFLATION PRESSURE SINGLE/DUAL		LOAD CAPACITY SINGLE/DUAL	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE	DUAL	KPA	PSI	KG	LBS
11R22.5	8.25	14	M	1065	279	144	142	720	105	2800 / 2575	6175 / 5675
		16	M			146	143	830	120	3000 / 2725	6610 / 6005
11R24.5	8.25	14	M	1116	279	146	143	720	105	3000 / 2725	6610 / 6005
		16	M			149	146	830	120	3250 / 3000	7160 / 6610
285/75R24.5	8.25	14	L/M	1056	283	144	141	760	110	2800 / 2575	6175 / 5675
		16	L/M			146	143	830	120	3000 / 2725	6610 / 6005
295/75R22.5	9.00	14	L/M	1020	298	144	141	760	110	2800 / 2575	6175 / 5675
		16	L/M			146	143	830	120	3000 / 2725	6610 / 6005
315/80R22.5	9.0	20	L	312	1076	156	153	850		4000 / 3650	

**Warehouse locations: Los Angeles, Phoenix, Tucson, Grand Prairie, Seattle, Boise**