

Single Stage – Gasoline

Compressor Pump:

- Integrated air/oil separator
- Integrated thermostatic bypass valve
- Integrated oil filter
- Poly Chain® belt drive system
- Easy-to-read oil level indicator
- High oil temperature shutdown

Engine:

- Electric start - battery and cables included
- Low-oil level shutdown

Frame:

- Powder coated steel frame with 1¼-inch roll cage, handle, 4-point lifting hook, winch point and tie-down anchors
- 15-inch pneumatic tires

Components:

- 10½-gallon aluminized steel fuel tank
- Oil cooler with guard
- Pressure gauge
- Ball valve controlled ¾-inch outlet
- Adjustable pilot valve changes engine RPM based on air demand

Limited Warranties:

- 3 year standard when RotorLub™ oil, filters and parts are used at the prescribed intervals
- 3 year Kohler engine



AR1-PK37-M



Air/oil separator, 19-0279; oil filter, 19-0278; and RotorLub™ 8000, AW-2200-0004 and AW-2200-0005

Powered by industry proven components, the patented Mi-T-M Rotary Screw Air Compressor works great in a wide variety of applications. This compact machine produces 115 CFM at 100 PSI, and the 10½-gallon fuel tank gives you the extended run time needed on many jobsites.

MODEL NUMBER	CFM @ PSI	DISPLACEMENT/ENGINE	COMPRESSOR	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AR1-PK37-M	115 @ 100	999cc Kohler CH1000 OHV	Single stage, rotary screw	Pneumatic	50.75x30.5x43.5in.	770 lb.	698 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODEL	PART NUMBER	DESCRIPTION	FITS MODEL
19-0278	Oil filter	AR1-PK37-M	AW-2200-0003	Pressure regulator assembly	AR1-PK37-M
19-0279	Air/oil separator	AR1-PK37-M	AW-2200-0004	Champion RotorLub™ 8000, 5-gallon pail	AR1-PK37-M
AW-2200-0001	Wye ball valve assembly	AR1-PK37-M	AW-2200-0005	Champion RotorLub™ 8000, 1-gallon bottle	AR1-PK37-M
AW-2200-0002	Water separator assembly	AR1-PK37-M	AX-0076	Skid feet	AR1-PK37-M