



250 mA 250 V ~ 1E4
20 mA 250 V ~ 5E4
250 mA 125/250 VAC UL/CSA

PRESSURE SWITCHES **SXP1**

ELECTRICAL FUNCTION	1 pole normally opened
PRESSURE RANGE: PRESSURE	+15 to +800 mbar 15-20 mbar: +/- 25% 21-25 mbar: +/- 15%
PRESSURE MEDIUM	Air or non hazardous gases only



2,5 (0,5) A 250 V ~ 1E4 (pmax: 2,5 bar)
1 A 250 V ~ 5E4 (pmax: 0,8 bar)
0,02 A 250 V ~ 5E4 (pmax: 0,8 bar)
2,5 A 125/250 VAC UL/CSA

2,5 (0,5) A 250 V ~ 1E4 (pmax: 2,5 bar)
0,5 A 250 V ~ 5E4 (pmax: 2,5 bar)
0,02 A 250 V ~ 5E4 (pmax: 2,5 bar)
2,5 A 125/250 VAC UL/CSA

PRESSURE SWITCHES **SX79**

ELECTRICAL FUNCTION	1 pole normally opened 1 pole normally closed
PRESSURE RANGE: PRESSURE	+15 to +2500 mbar +/- 10% +15 to +2500 mbar +/- 15%
PRESSURE MEDIUM	Pressure: Non hazardous gases - Liquids (up to 24V only) Vacuum: Non hazardous gases



16 (4) A 250 V ~ 5E4
10 (3) A 250 V ~ 5E4
3 (1) A 250 V ~ 5E4

PRESSURE SWITCHES **SXM3**

ELECTRICAL FUNCTION	1 pole normally opened 1 pole normally closed 1 pole change over
PRESSURE RANGE: PRESSURE	+30 to +2500 mbar +/- 10%
PRESSURE MEDIUM	Pressure: Non hazardous gases - Liquids Vacuum: Non hazardous gases