

ATC-2000

Advanced Traffic Controller



The ATC-2000 is the rack-mounted version of Peek Traffic's ATC controller. These controllers are designed to be modular and based on the widest range of traffic controller standards in the world. Emphasizing ease-of-use and easy adaptability, the ATC-2000 traffic controller features Peek Traffic's latest ATC engine board, a full line of communications options including multiple serial ports, multiple Ethernet ports, multiple USB ports, and a range of I/O options. The ATC-2000 takes all of the capabilities of the Peek Traffic ATC-1000 controller and places them into a form that is compatible with standard cabinet racks. At 4" in height and 17" width (43.2 cm), with 19" wide mounting brackets (28.3 cm), the ATC-2000 will fit into a variety of standard cabinet styles, CalTrans 330 and also Peek's own ASTC-12 Central Business District cabinet, the enclosure used so successfully throughout New York, San Salvador and Ecuador. Fully programmable from the front panel, via USB data base download, via ATC Link® direct connection, via IQ Central and Spinnaker, Peek's central systems using either serial or Ethernet connections, the ATC-2000 controller is a powerful new option that can be used wherever NTCIP and ATC compatibility is required.

Peek Traffic's ATC line of controllers are the first in the world to include both interval-based and phase-based (NEMA) traffic engines running side-by-side. In fact with these controllers, it is possible to transition between phase-based and interval based operation on the fly, with no interruption other than a programmable short stint in Red Rest operation.



The ATC-2000 controller uses NTCIP communications and is entirely compatible with Peek Traffic's IQ Central® and Spinnaker traffic management systems, as well as TransCore's TranSuite® and MIST central software.

With its powerful processor, wide range of interconnection hardware, and easy-to-perform firmware update capability, the ATC-2000 is a controller that can be relied upon to stay current with the latest ITS management schemes and algorithms.

Features

- 40 character x 16 line Backlit LCD Display with optional heater
- Linux Operating System with memory management for process isolation
- Compliant with NTCIP 1201, 1202
- ATC 5201 Modem Slot
- 300MHz Freescale Power Quix 2 processor
- Four independent 100 Base-T Ethernet ports
- Two high speed USB port
- 32 key soft-touch keypad for front panel programming
- Speaks NTCIP protocol—Spinnaker, TranSuite & MIST Central Software

Specifications

Dimensions	48.3 cm wide x 26.7 cm deep x 17.8 cm tall (19" x 10 1/2" x 7")
Weight	9 to 11 pounds (4 to 5kg) depending on which I/O modules and comms hardware are installed
Power Requirements	89 to 135VAC 50Hz/60Hz ± 3 Hz
Environment	-40 °F to + 176°F or -40°C to +80°C 0-95% relative humidity Exceeds NEMA/ATC/CALTRANS TEES 2009
Memory	16MB Flash memory standard, 64MB SDRAM— 1MB SRAM
NTCIP Compliance	The traffic application software is NTCIP software compliant, ensuring easy integration into any NTCIP or ITS traffic control system. The ATC controllers also interface with IQ Central®, Peek Traffic's central control system, which interfaces to both legacy controllers as well as other NTCIP compliant devices.
Firmware Updates	Via USB port or via IQ Link
I/O Module	Supports 2070-2A 2070-2E TS2 Type 1
Applications	Greenwave Voyage

Operating System Linux v2.6.2.0

Computer Interfacing Intersection configuration programming is easily performed in the field, using the provided laptop computer interface software (ATC Link). ATC Link can be connected directly via an Ethernet or a serial cable, or it can be used to store the configuration on a portable USB "flash drive," which can then be downloaded to the device in the field in seconds. Or programming may be downloaded across a network via an NTCIP compliant central system, such as IQ Central or Spinnaker.

Communications:

Connectivity is easily achieved using a variety of communications options:

- Four 10/100 Base-T Ethernet ports
- Two high-speed USB port
- One RS485 Port for SDLC
- Three RS232 Ports for serial communication
- 2070 Modem slot

These physical port options allow for interfacing to a variety of communications infrastructures:

- Existing 1200 baud twisted pair
- High-speed serial (RS232) up to 115kbps
- Fiber-optic modems
- Wireless systems
- LAN/WAN applications

Additional Features:

- Power Monitoring
- Power Supply voltages available through the LCD
- Internal Temperature Sensor



Peek Traffic Corporation
A Signal Group Company
5401 N Sam Houston Pkwy W
Houston, TX 77086
(281) 453-0200
www.peaktraffic.com

About Signal Group – covers a broad range of quality turnkey traffic control products and services. Signal Group products have helped to make motorists around the world safer and their travels more pleasant and efficient. This expertise, experience, and breadth of product lines has made Signal Group one of the most respected and recognized leaders in the traffic control marketplace. The information contained in this publication is presented for informational purposes only, and while every effort has been made to ensure its accuracy, the information is not to be construed as warranty or guarantee, express or implied, regarding the products or services described herein or their use or applicability. No license is granted by implication or otherwise to any of Signal Group's intellectual property. Signal Group reserves the right to alter or revise any of its products or published technical data related thereof at any time without notice. ©2012 Signal Group.