

FLEETCLEAN SYSTEMS LLC

401.356.4156 www.fleetcleansystems.com sales@fleetcleansystems.com

Specifications

ATTRIBUTE	DESCRIPTION
Physical Form	Clear Liquid
Odor	Citrus
Solubility	Not Soluble in Water
Foam	None
Viscosity	Water like
pH (Typical)	Not Applicable
Flash Point	154F°

Dilution Ratios

Use	Dilution
Extraction Solvent	Straight

DOT Classification:

Regulated

Available In

PART #	SIZE
120618	1 Gal.
120617	5 Gal.
120615	55 Gal.

ASPHALT XL-71

Tech Data Sheet

Newly developed Asphalt XL-71 is a high flash extraction solvent for bituminous extraction testing in vacuum extraction and centrifuge equipment. A safe, effective alternative to chlorinated solvents and is approved by or meets the product specifications for states requiring high flash solvents. Also works quickly and effectively to clean asphalt equipment.

Benefits

- Safer than methylene chloride and trichloroethylene
- Passed total toxic organic scan for toxic wastes
- ◆ Conforms to specifications outlined in AASHTO T164 for
- asphalt extraction solvents
- ◆ Flash Point of 154°F (close cup)
- ◆ Biodegradable
- Lower cost, more stable price alternative to d'limonene products on the market

Applications

- Asphalt Extraction
- Cleaning asphalt equipment and tools

Precautions

CONSIDERED NON-TOXIC WHEN USED ACCORDING TO
INSTRUCTIONS. NOT MEANT TO BE MIXED OR DILUTED WITH WATER.
 CONSULT THEPRODUCT SAFETY DATA SHEET FOR GENERAL SAFETY
GUIDELINES.

Note: Cleaning effectiveness is affected by: temperature, concentration, dwell time, water hardness, and soap application pressure. Soap concentration may be adjusted to compensate for changes in these conditions.