Work Pro® Series | Single or Two Stage Electric/Gasoline

The high performing Work Pro Series is offered in an 8-gallon electric or gas-driven air compressor. Available as a single or two-stage compressor it can power everything from impact wrenches and nail guns to paint sprayers and staplers.



Compressor Pump

- Splash oil lubricated aluminum crankcase
- Stainless-steel braided discharge hose
- Oil level sight indicator

Motor

- Thermal overload motor protection

Frame

- Powder coated 8-gallon twin tank receivers
- 3/16-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard
- 10-inch flat-free tire (Two-stage models have two tires)

Components

- Regulator and two gauges for tank and outlet pressure
- Drain and pressure relief valves
- Fly wheel
- Industrial-grade pressure switch (Electric model)
- Quality pilot valve unloader (Gasoline models)









Electric Model								
Model Number	CFM @ PSI	Horsepower/Motor	Compressor	Tank Size	Plug Type	Dimensions (LxWxH)	Ship Wt.	Net Wt.
AM1-PE15-08WP	7.3 @ 90	1.5 HP, 115V, 13.2A	Single stage, aluminum	8-gallon	NEMA 5-15P	44.5x18.5x25in.	160 lb.	140 lb.

AMIT I ETO OOMI	7.0 @ 00	1.0111, 1104, 10.27	Olligio otago, alaminam	o gallon	TVLIVI/ CO TOI	11.0X10.0X20III.	100 10.	1 40 10.
Gasoline Models								
Model Number	CFM @ PSI	Displacement/Engine	Compressor	Tank Size	Engine Idle Control	Dimensions (LxWxH)	Ship Wt.	Net Wt.
AM1-PH06-08WP	9.0 @ 90	196cc Honda GX200 OHV	Single stage, aluminum	8-gallon	Pneumatic	44.5x18.5x27in.	160 lb.	135 lb.
AM1-PM06-08WP	9.0 @ 90	212cc Mi-T-M OHV	Single stage, aluminum	8-gallon	Cable throttle	44.5x18.5x27in.	160 lb.	135 lb.
AM1-PH65-08WP	13.9 @ 90	196cc Honda GX200 OHV	Single stage, aluminum	8-gallon	Pneumatic	44.5x18.5x27in.	170 lb.	145 lb.
AM1-PM65-08WP	13.9 @ 90	212cc Mi-T-M OHV	Single stage, aluminum	8-gallon	Cable throttle	44.5x18.5x27in.	170 lb.	145 lb.
AM2-PH09-08WP	17.2 @ 175*	270cc Honda GX270 OHV	Two stage, aluminum	8-gallon	Pneumatic	44x26x31in.	200 lb.	175 lb.
AM2-PM09-08WP	17 2 @ 175*	300cc Mi-T-M OHV	Two stage aluminum	8-nallon	Pneumatic	44y26y31in	200 lh	175 lh

^{*}Equipped with 150-PSI maximum rated regulator.

Accessories & Options:				
Part Number	Description	Fits Models		
70-0357	Engine oil drain extension - 14-inch flexible drain hose makes oil changes clean and easy	Single stage models		
70-0358	Engine oil drain extension - 14-inch flexible drain hose makes oil changes clean and easy	Two stage models		
AW-6000-1002	Equipment cover - Keeps your equipment clean, dry and looking like new	All models		
AX-0002	Auto drain/regulator/plastic bowl - Drains moisture from air system	AM1-PE15-08WP		
AX-0003	Manual drain/regulator/metal bowl - Drains moisture from air system	All models		
AX-0015	Electric start - battery, box and cables not included	AM2-PH09-08WP		
IX-0055	Remote start/choke - 6-ft. wire extension for key switch. You will also need to order electric start option, AX-0015	AM2-PH09-08WP		
IX-0059	Remote start/choke - 6-ft. wire extension for key switch, sealed cable. You will also need to order electric start option, AX-0015	AM2-PH09-08WP		

MARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.