WAGGOTT CAMS

									<i>I</i> A O O I I I										
No.	S T	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS	
	Α			Advertised		@.050"		Cam		Valve		@T.D.C.							
	G E	ln.	Ex.	ln.	Ex.	ln.	Ex.	ln.	Ex.	ln.	Ex.	ln.	Ex.	ln.	Ex.	ln.	Ex.		
638	STD	24-75	55-28	279	263	182	176	.230	.230			.022	.028	.008	.012	111	106		
339	1	18-58	70-30	249	280	184	194	.230	.248			.028	.052	.010	.012	109	110		
666	2	25-64	70-30	269	282	201	202	.263	.264			.038	.032	.010	.012				
198	3	38-78	80-38	296	298	226	236	.280	.280					.010	.012				
163	4	42-85	82-42	309	304	244	244	.292	.292					.010	.012				
297	5					250	250	.340	.338			.121	.115	.008	.010				

CODE: NISSAN E15

PERFORMANCE - 44HFSC2V NOTES: STD TURBO IS THE SAME AS STD

STANDARD - 44SOHC BILLETT - NIL

EXCHANGE - DEP E15

E15

NISSAN