

Our company is based on the belief that our customer's needs are of the utmost importance. We are committed to meeting those needs as timely and accurately as we can, and we stand behind our products with a 100% return guarantee. We would welcome the opportunity to earn your trust and deliver you the best product we can to meet your needs.



Toll Free Call (USA & CAN): 1-855-35-TRUCK (87-825)

We Deliver Throughout the U.S.A. / Alaska and Canada, and will ship worldwide



ATP519 TUBELESS

Wheel position: For drive wheels.

Application: For improved or mixed road surface

in good and bad conditions.

Characters: Tough blocks provide strong traction and

off-road performance. Special tread design effectively improves self-cleaning performance.

Deep grooves enable the tyre to have a high mileage.



SIZE	RIM	PLY RATING	SPEED	NEW TYRE DESIGN DIMENSION/mm			LOAD INDEX		INFLATION PRESSURE SINGLE/DUAL		LOAD CAPACITY SINGLE/DUAL	
				SECTION WIDTH	OVERALL DIAMETER				51115-21			
					HIGHWAY	TRACTION	SINGLE	DUAL	KPA	PSI	KG	LBS
11R/22.5	8.25	14	К	279		1065	144	142	720 / 720	105 / 105	2800 / 2650	6170 / 5840
		16	К			1065	146	143	830 / 830	120 / 120	3000 / 2725	6610 / 6005
11R/24.5	8.25	14	К	279		1116	146	143	720 / 720	105 / 105	3000 / 2725	6610 / 6005
		16	K			1116	149	146	830 / 830	120 / 120	3250 / 3000	7160 / 6610
12R/22.5	9.0	16	L	300	1085		150	147	830 / 830	120 / 120	3350 / 3075	7390 / 6780
		18	L				152	149	930 / 930	135 / 135	3550 / 3250	7820 / 7160
285/75R/24.5	8.25	14	K	283		1056	144	141	760 / 760	110 / 110	2800 / 2575	6175 / 5675
		16	К			1056	147	144	830 / 830	120 / 120	3075 / 2800	6780 / 6175
295/75R/22.5	9.0	14	К	298		1020	144	141	760 / 760	110 / 110	2800 / 2575	6175 / 5675
		16	К			1020	146	143	830 / 830	120 / 120	3000 / 2725	6610 / 6005