


# 3000 & 5000-Watt Gasoline



Perfect for powering a multitude of tools on any jobsite, the 3000-watt and 5000-watt generators were designed with contractors in mind. Long run times mean you don't have to take a refuel break.



## Alternator

- Total harmonic distortion (THD) less than 5%
- 100% copper windings

## Frame

- Heavy-duty powder coated wraparound frame with 1-inch steel tubing
- Angled isolator design features four neoprene isolators

## Components

- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Large low tone mufflers
- Fuel shut-off valve
- Easy-to-read fuel gauge
- Heavy-duty industrial air cleaner


## Miscellaneous

- USDA/USFS-approved spark arrestors

GEN-5000-0MHO



# 3000 & 5000-Watt Gasoline




Model Number	GEN-3000-1MH0	GEN-3000-1MK0	GEN-5000-0MH0	GEN-5000-0MK0
Max. AC Output	3000 watts	3000 watts	5000 watts	5000 watts
Rated AC Output	2450 watts	2450 watts	4400 watts	4400 watts
Displacement/Engine	163cc Honda GX160 OHV	208cc Kohler CH270 OHV	270cc Honda GX270 OHV	277cc Kohler CH395 OHV
Alternator	Brushless 120V, 60Hz	Brushless 120V, 60Hz	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz
Max. Amps (120V/240V)	25.0	25.0	41.7/20.8	41.7/20.8
Cont. Amps (120V/240V)	20.4	20.4	36.7/18.3	36.7/18.3
Receptacles	(1) 120V, 20A GFCI duplex	(1) 120V, 20A GFCI duplex	(2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock (1) 120V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock (1) 120V, 30A twist lock
Circuit Breakers	(1) 20A push-button	(1) 20A push-button	(2) 20A toggle circuit breakers, single pole (1) 20A toggle circuit breaker, double pole (1) 30A toggle circuit breaker, single pole	(2) 20A toggle circuit breakers, single pole (1) 20A toggle circuit breaker, double pole (1) 30A toggle circuit breaker, single pole
Rated Speed	3600 RPM	3600 RPM	3600 RPM	3600 RPM
Decibel Rating	74.8	74.8	73.8	73.8
Fuel Capacity	2.6 gallons	2.6 gallons	5.7 gallons	5.7 gallons
Run Time (At Full Load)	7.4 hours	7.4 hours	6.8 hours	6.8 hours
Full Power Switch	No	No	Yes	Yes
Dimensions (LxWxH)	25x18x18in.	25x18x18in.	29x19.75x22.5in.	29x19.75x22.5in.
Ship Wt.	146 lb.	146 lb.	198 lb.	198 lb.
Net Wt.	130 lb.	130 lb.	176 lb.	176 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

### Accessories & Options:

Part Number	Description	Fits Models
32-0915	RV generator adapter - 30A/125V female/male. Use to connect RV cordsets to 30A generators	5000-watt models
AW-5090-0003	Lifting hook - For easier portability, folds down and out of the way when not in use	5000-watt models
AW-5740-0009	Wheel kit - For easier mobility, two flat-free tires and rubber gripped handles	5000-watt models
GX-0004	Hour meter - Displays number of hours the unit has been in operation	5000-watt models



GFCI 5-20R



NEMA L5-30R  
120VAC  
GEN-5000 Models



NEMA L14-20R  
120V/240V  
GEN-5000 Models

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).