

6000-Watt – Diesel



GEN-6000-0MKD

Alternator:

- Total harmonic distortion (THD) less than 5%
- 100% copper windings

Frame:

- Heavy-duty powder coated wraparound frame with 1-inch steel tubing
- Angled isolator design features six neoprene isolators

Components:


- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Fuel shut-off valve
- Easy-to-read fuel gauge
- Voltmeter/hour meter
- Heavy-duty industrial air cleaner

Limited Warranties:

- 2 year alternator
- 3 year Kohler engine

Certification:

- CSA Certified



GFCI 5-20R



NEMA L14-20R
120V/240V



NEMA L5-30R
120VAC

Portable gasoline generators tend to be the most popular among contractors, but this portable diesel generator provides heavy-duty power for long life and extended operation. Plus, it costs less to operate than its gasoline counterparts.

MODEL NO.	GEN-6000-0MKD
MAX. AC OUTPUT	6000 watts
RATED AC OUTPUT	5000 watts
HORSEPOWER/ENGINE	9.1 HP Kohler KD440 OHV with electric start - battery included
ALTERNATOR	Brushless 120V/240V, 60Hz
MAX. AMPS (120V/240V)	50.0/25.0
CONT. AMPS (120V/240V)	41.7/20.8
RECEPTACLES	(2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock (1) 120V, 30A twist lock
CIRCUIT BREAKERS	(1) Main circuit breaker (2) 20A toggle circuit breakers, single pole (1) 20A toggle circuit breaker, double pole (1) 30A toggle circuit breaker, single pole
RATED SPEED	3600 RPM
DECIBEL RATING	85.0
FUEL CAPACITY	2.6 gallons
RUN TIME (AT FULL LOAD)	6.8 hours
DIMENSIONS (LxWxH)	29x21.62x22.5in.
SHIP WT.	295 lb.
NET WT.	273 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODEL	PART NUMBER	DESCRIPTION	FITS MODEL
32-0915	RV generator adapter	GEN-6000-0MKD	AW-5740-0006	Wheel kit with flat-free tires	GEN-6000-0MKD
AW-5090-0007	Lifting hook	GEN-6000-0MKD	AW-6000-1002	Equipment cover	GEN-6000-0MKD