

WLP Series



WLP-20-0M10

WLP Series recycle systems combine enhanced design with state-of-the-art technology to offer:

- Quality recycled wash water without common odor problems
- Easy operation and maintenance
- Poly skid is constructed of hardened polymer to be non-corrosive and can be easily lifted and moved with a forklift from all four sides
- CSA approved control panel which meets the requirements of the US and Canadian standards for an Industrial Control Panel

MODEL NUMBER	FLOW RATE	MEDIA FILTER (CUSTOM MIX)	CARTRIDGE FILTER	CARBON FILTER (DEGASSED)	POWER REQUIREMENTS	AIR REQUIRED	DIMENSIONS (LxWxH)	SHIP WT.
WLP-08-0M10	0-8 GPM	350 lb.	100 sq. ft.	110 lb.	230V, 1Ø, 21.0A	-	6ft.x5ft.x52in.	1475 lb.
WLP-20-0M10	0-20 GPM	550 lb.	400 sq. ft.	110 lb.	230V, 1Ø, 25.0A	-	8ft.x5ft.x52in.	2435 lb.
WLP-20AB-0M11*	0-20 GPM	550 lb.	-	110 lb.	230V, 1Ø, 25.0A	60 to 100-PSI	8ft.x5ft.x52in.	2435 lb.
WLP-20AB-0M31*	0-20 GPM	550 lb.	-	110 lb.	230V, 3Ø, 13.0A	60 to 100-PSI	8ft.x5ft.x52in.	2435 lb.
WLP-30-0M10	0-30 GPM	500 lb.	400 sq. ft.	110 lb.	230V, 1Ø, 30.0A	-	8ft.x5ft.x52in.	2735 lb.
WLP-40-0M10	0-40 GPM	900 lb.	600 sq. ft.	165 lb.	230V, 1Ø, 30.0A	-	(2) 8ft.x5ft.x60in.	3200 lb.
WLP-40AB-0M11*	0-40 GPM	900 lb.	-	165 lb.	230V, 1Ø, 33.0A	60 to 100-PSI	7ft.x9ft.x60in.	3100 lb.
WLP-40AB-0M31*	0-40 GPM	900 lb.	-	165 lb.	230V, 3Ø, 17.0A	60 to 100-PSI	7ft.x9ft.x60in.	3100 lb.

*Auto-backwash models (air required 60 to 100-PSI)

230/208/460V 3-phase available on all models as options.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
32-0538	pH probe - Keeps the water at an appropriate pH level so the germicide is effective at killing bacteria and controlling odor	All models
32-0540	ORP probe - Measures and injects a germicide to control odor by killing odor-causing bacteria	All models
32-0693	pH probe (self-cleaning) - Keeps the water at an appropriate pH level so the germicide is effective at killing bacteria and controlling odor	All models
55-1887	Check valve, 2-inch - Holds prime in suction line	All models
AT-4007	Replacement air filter - Moisture trapping replacement filter	Auto-backwash models

We recommend a Mi-T-M Air Compressor (AM1-HE02-05M) for use with the WLP and WCP Series Auto-Backwash models. Consult your Mi-T-M Authorized Dealer for more information.



AM1-HE02-05M

The AM1-HE02-05M features:

- Quality single stage compressor
- 120V single-phase 60Hz motor with 15-amp plug
- Thermal overload motor protection
- 5-gallon powder coated twin tank assembly
- Stainless-steel braided discharge hose
- Regulator and two gauges for tank and outlet pressure
- Industrial interchange quick connect fittings
- Powder coated steel frame design with rubber handle

MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	PLUG TYPE	DIMENSIONS	SHIP WT.
AM1-HE02-05M	4.2 @ 90	2.0 HP, 120V, 15.0A	NEMA 5-15P	20.5x15.5x17.5in.	70 lb.