

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
								Advertised		@.050"		Cam						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
404	1	20-57	62-18	256	260	205	206	.282	.284	.423	.426	.036	.034	HYD	HYD	109	111	
408	2	26-63	68-24	270	272	208	209	.280	.280	.420	.420	.040	.037	HYD	HYD	109	110	
409	3	30-70	70-30	280	280	217	217	.285	.285	.428	.428	.052	.048	HYD	HYD	108	111	
410	4	38-78	78-38	295	295	226	226	.305	.305	.458	.458	.060	.055	HYD	HYD	109	111	
417	5	43-81	77-41	304	298	241	240	.333	.333	.500	.500	.086	.083	HYD	HYD	111	108	

CODE: FORD 250 CYL
 PERFORMANCE - 46G
 STANDARD - 46S
 BILLET - EP63
 EXCHANGE - DEP 250

NOTES: MOST HAVE CAST ON INLET MAINFOLD
 2V HAVE BOLT ON INLET MANIFOLD

250 CYL-PRE XFLOW

ROCKER RATIO 1.5

FORD