

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
158	STD	30-70	74-32	280	286	200	198	.250	.250	.400	.400			.008	.012	108	110	
602	1	29-69	70-30	278	280	199	199	.276	.276	.434	.432			.008	.010	109	111	
296	2	32-74	80-40	286	301	220	223	.252	.255	.393	.396			.010	.012	111	110	
461	2	28-70	77-35	278	292	208	225	.290	.290	.454	.452			.010	.012	111	111	
501	3	43-80	80-43	303	303	224	224	.276	.276	.434	.432			.008	.010	108	110	
198	4	38-78	80-38	296	298	226	236	.280	.280	.438	.436			.010	.012	110	111	
161	4	37-78	94-51	295	325	225	227	.290	.290	.454	.454			.010	.012	111	111	
163	5	42-85	82-42	309	304	244	244	.292	.292	.457	.455			.010	.012	112	110	
138	5	48-85	80-45	313	305	232	230	.265	.267	.414	.415			.010	.012	108	107	
602	1	29-69	70-30	278	280	199	199	.276	.276	.434	.432			.008	.010	109	111	TURBO
198	2	36-80	83-35	296	298	226	236	.280	.280	.438	.436			.010	.012	112	114	TURBO

CODE: FORD 2LTR

PERFORMANCE -44GOHC
 STANDARD -44SOHC
 BILLET -EP26
 LASH CAPS -LC2LTR
 EXCHANGE -DEP 2LTR
 ROCKERS -CFI

NOTES: STD ROCKERS OR CAMTECH ROCKERS ONLY SHOULD BE USED
 STD SPRINGS OK UP TO STAGE 3
 ALWAYS CHECK WEAR POSITION ON ROCKER ARMS
 STAGE 3 & BIGGER REGRINDS MAY REQUIRE LASH CAPS
 PT#C2LTR

ROCKER RATIO 1.6

2 LTR

FORD