NISSAN FIGARO

LUBRICANTS & FLUIDS - CAPACITIES AND SPECIFICATION

Engine oil: Semi synthetic oil 10W30 or 10W40 (e.g. Mobil Super) Fully synthetic oil 0W40 or 5W40 (e.g. Mobil 1) Refilling capacity - approx 3 litres

Transmission: Automatic Transmission Fluid (ATF) to specification Dexron3 (usually indicated Dexron111 on the pack) (Dexron2 is acceptable if 3 not available) Capacity - approx 6.5 litres

Power steering: Automatic Transmission Fluid (ATF) to specification Dexron3 (usually indicated Dexron111 on the pack) (Dexron2 is acceptable if 3 not available) Dextron fluids can be red (usually) or golden and can safely be mixed.

Brake fluid : Fluid to DOT 3 or 4 specification (DOT 2 is also acceptable) Under no circumstances should silicon based fluid to DOT 5 specification be used

General lubrication: engine oil

Brake contact parts (not hydraulic parts) Copper based grease or Mintex Cera Tec

Bearings and general greasing : Lithium based high temperature grease

Coolant: 50% mixture of ethylene glycol or propylene glycol antifreeze or pre-mixed coolant without dilution Normal antifreeze - change every 2 years Long life antifreeze - change every 5 years System capacity - approx 4 litres