


SXA4


TYPICAL APPLICATIONS	High pressure cleaners, ironing steam generators, industrial machines, cutters
FUNCTIONS	■ DPST, illuminated or not
PROTECTION DEGREE	IP 54, IP 55 for version with silicone
CYCLE No.	10.000
CUT OUT	30x22 mm
AMBIENT TEMPERATURE	125 °C
GWT	850 °C
GWT NO FLAME (<2sec)	750 °C on demand




S	X	A	4		?		?
DRAWING					**TERMINAL**		**FUNCTION**


O-RING






GASKET






1 Standard

4 With silicone




3 Standard


5 With silicone





2




8







POS.	DIM.	TOL.
K	1.2	±0,1
H	R.0.6	+0.2
G	R.3.5	-0.1
F	5.5	+0.2
E	0.7/3.5	
D	26.6	±0.1
C	33.6	±0.1
B	22	+0.1
A	30	+0.2



POS.	DIM.	TOL.
Z	0.7/3.5	
Y	22	+0.1
X	30	+0.2

TERMINAL	FUNCTION	RATING	FRAME COLOUR	BUTTON COLOUR ON	BUTTON COLOUR OFF	MARKING COLOUR	MARKING ON	MARKING OFF	LENS COLOUR		
S	X	A	4							0	0

RATING

8

Function 2

16 (8) A / 250 VAC
10 (6) A / 250 VAC - 5E4
10 (4) A / 400 VAC
T125/55 °C
EN 61058

16 A - 125 / 250 VAC
3/4 HP - 125 / 250 VAC
T105 °C
UL 1054

Function 8

16 (8) A / 250 VAC
10 (6) A / 250 VAC - 5E4
T125/55 °C
EN 61058

16 A - 125 / 250 VAC
3/4 HP - 125 / 250 VAC
T105 °C
UL 1054

9

Function 2 - 8

12 (10) A / 250 VAC - 5E4
T85 °C
UL 1054

FRAME COLOUR

1 black

X ? custom

BUTTON COLOUR

ON **?** OFF **?**

1 black

X ? custom

MARKING COLOUR

?

0 none

2 white

X ? custom

MARKING

ON **?** OFF **?**

Marking ON

0



2



3



5



X



Marking OFF

0



1



4



X



LENS COLOUR

? **0** **0**

0 none

ILLUMINATED

G red

L white

X ? custom