



## FLEETCLEAN SYSTEMS LLC

401.356.4156

[www.fleetcleansystems.com](http://www.fleetcleansystems.com)  
[sales@fleetcleansystems.com](mailto:sales@fleetcleansystems.com)

### Specifications

Attribute	Description
Physical Form	Blue Liquid
Odor	Acidic
Solubility	Complete in Water
Foam	Low-Moderate
Viscosity	Water-like
pH (typical)	2.0
Flash Point	Not Applicable

### Dilution Ratios

Use	Dilution
Heavy	5:1 - 10:1
Moderate	10:1 - 15:1
Light	15:1 - 25:1

**DOT Classification:**  
Not Regulated

### Available In:

Part #	Size
111237	5 Gal.
111235	55 Gal.
111239	Bulk
11295	Kit 6 gal



# SUPERSONIC PRE-SOAK

## Tech Data Sheet

An aggressive low pH presoak that is uniquely formulated for the fleet cleaning industry. It cleans and brightens aluminum while having the capability to clean surfaces where finger prints, greases, and oils are present. Supersonic Pre-Soak is very versatile and can be paired up with multiple HCS detergents.

### Benefits

- Safe on painted surfaces
- Helps eliminate brushing
- 100% Biodegradable
- Helps break down carbon based soils like oils and greases as a presoak
- Removes paint oxidation

### Applications

- Low pH presoak in a touchless 2-step fleet washing process
- Can be paired with the following 2nd Step Detergents: Fleet Brite, Dynaclean & Bright, Film Fighter, and Pro-Wash
- Wheel Cleaning
- Brightens aluminum

### Precautions

- Contains sulfuric acid. NOT to be used on a polished aluminum. Do NOT allow to dry on glass. Consult Safety Data Sheet for further safety information

---

**Note:** Cleaning effectiveness is affected by: temperature, concentration, dwell time, water hardness, and soap application pressure. Soap Concentration may be adjusted to compensate for changes in these conditions.