

22x Outdoor PTZ Dome 470 TVL IP-66 Day/Night



Model	iPTZC22DNSN
Image Sensor	NTSC
Horizontal Resolution	470 TVL
S/N Ratio	More than 50dB
Min Illumination	0.51 ux(External IRLED on 0lux)
Lens	3.9 ~ 89.5 mm
Lens Electronic Shutter	1/60 to 1/100000 sec NTSC
White Balance	Auto White Balance
Electronic Shutter	ON/OFF Switchable
Auto Gain Control	Auto White Balance
Black Light Compensation	ON/OFF Switchable
Control Interface	RS485
Focus way	Auto Focus
Video Output	1.0V p-p 75 (BNC)
Power Internal Camera	DC12V-10% + 15% More than 850 mA DC Power
Input voltage	AC24V 50&60HZ
Input Power	Pan/tilt 10VA
Heater power	AC24V 22W
Consumption	
Heat Action Range	NO. 10* C +/-5 OFF: 26* C +/-5
Angle available	Pan: 0* - 350* tilt 0*90*
Moving velocity	Pan 12* /s tilt 12* /s
Limitation	Pan/tilt adjustable
Max size of lens Adding camera	9" 170x75x70mm
Structure	Housing: DMC Pan/tilt: aluminum Optical cover: Aerylic