



























AacerFlex™

AacerFlex™ incorporates precision engineered pads that integrates load bearing ability with enhanced athletic performance. AacerFlex can be specified for multipurpose rooms, competitive sports applications and dance/aerobics. Available in AacerFlex[™], AacerFlex[™] TP, and AacerFlex[™] EN-DIN with 12mm TriPower™ Pads and EcoDin Pads.



Certified









Green Status **LEED Contributors**







FSC Maple - MRc7 FSC SubFloor Components - MRc7 FO - 42 Regional materials MRc5.1 & 5.2

Optional Versions

Aerobics and dance

50 duro blue, 60 duro orange, 70 duro red TriPower AacerFlex, EcoDin, 1/2" TriPower Pad

Resilience

Aacer TriPower Pad

Slab Depression

¾" (19mm) TriPower Pad, AacerFlex

25/32" (20mm) flooring - 2 1/2" (64mm) 33/32" (26mm) flooring - 2 3/4" (70mm)

1/2" (12mm) TriPower Pad

25/32" (20mm) flooring - 2 1/4" (57mm) 33/32" (26mm) flooring - 2 1/2" (64mm)

7/16" (11mm) EcoDin Pad, 1/2" TriPower Pad

25/32" (20mm) flooring - 2 1/8" (55mm) 33/32" (26mm) flooring - 2 1/8" (73mm)

Subfloor Construction

Plywood

System Type

Floating System

Testing Laboratory








U.S. Patent#


Warranty


Lifetime available

WALL BASE



THRESHOLD





AacerFlooring.com

(877) 582-1181