

# WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
656	1	16-55	67-15	252	257	195	202	.268	.260	.402	.390	.023	.020	HYD	HYD	110	112	GAS
404	2	20-57	62-18	256	260	205	206	.282	.284	.423	.426	.036	.034	HYD	HYD	109	111	
653	3	32-70	80-30	281	289	214	223	.310	.292	.465	.438	.048	.045	HYD	HYD	109	115	
409	3	30-70	70-30	280	280	217	217	.285	.285	.428	.428	.052	.048	HYD	HYD	108	111	
474	4	36-80	82-33	294	295	224	234	.310	.324	.465	.486	.060	.055	HYD	HYD	109	114	
544	5	41-74	90-39	295	309	233	244	.324	.340	.486	.510	.070	.065	HYD	HYD	108	115	
490	6	39-87	90-37	306	307	242	234	.348	.335	.522	.503	.065	.065	HYD	HYD	116	112	
606	7	68-78	80-68	327	328	249	256	.330	.340	.495	.510	.095	.092	HYD	HYD	103	113	
273		23-70	66-20	273	266	221	220	.284	.284	.410	.406	.053	.048	.016	.020	109	112	
233		29-56	60-27	266	268	216	216	.265	.265	.383	.383	.050	.045	.015	.015	107	107	
466		32-64	68-30	276	278	249	250	.338	.339	.487	.487	.105	.101	.020	.022	107	109	
467		34-63	73-32	277	285	249	258	.360	.365	.514	.522	.113	.092	.026	.026	106	110	

**CODE: CHRYSLER 273/318**

PERFORMANCE - 48G

STANDARD - 48S

BILLET - EP18

EXCHANGE - DEP 273/318

HYD FOLLOWERS -RHT2011

**NOTES:** 273 HAS ADJUSTABLE ROCKERS - SOLID FOLLOWERS

318-360 HAS NON ADJUSTABLE ROCKERS-HYD FOLLOWERS

**273/318**

**ROCKER RATIO 1.5**

**CHRYSLER**