

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
439	1	36-70	72-36	286	288	215	219	.295	.295	.460	.458	.048	.045	.012	.014	108	112	
107	2	32-68	68-30	280	278	228	227	.295	.295	.454	.454	.065	.058	.018	.018	108	108	
212	3	35-72	73-34	287	287	230	230	.277	.277	.428	.428	.065	.060	.015	.015	108	110	
537	4	53-91	95-50	324	325	240	242	.298	.298	.477	.477	.075	.073	HYD	HYD	108	112	
215	4	32-75	76-31	287	287	243	240	.292	.292	.452	.449	.075	.073	.015	.018	113	111	
601	5	30-75	83-30	285	293	239	249	.333	.346	.521	.540	.075	.075	.012	.014	112	116	
104	6	47-78	80-48	305	308	251	254	.325	.330	.500	.506	.104	.104	.020	.022	105	108	
250	6	40-84	86-44	304	310	255	259	.325	.330	.500	.506	.109	.109	.020	.022	107	109	
467	6	34-63	73-32	277	285	249	258	.360	.365	.550	.558	.113	.092	.026	.026	106	110	
178	7	46-81	84-45	307	309	264	265	.350	.350	.540	.538	.105	.090	.020	.022	107	109	

CODE: HOLDEN V8 SOLIDS
 PERFORMANCE - 48G
 STANDARD - 48S
 BILLET - EP5
 EXCHANGE - DEP 253/308

ROCKER RATIO 1.6

V8 SOLIDS

HOLDEN