


# ANSI Grade 1 156.3 Fire Exit Hardware Rim Type & Vertical Rod Exit Devices



**F8000 Fire Rated  
F8100 Fire Rated**

**10 YEAR  
WARRANTY**



**F8000 Rim Type  
Fire Rated Exit Device**  
Shown in Duro Bronze

**F8100 Vertical Rod  
Fire Rated Exit Device**  
Shown in Aluminum US28

## PRODUCT FEATURES

- Will cover stock hollow metal doors with 161 cutout.
- Outside Pull or Lever trim available (See Trim page for options).
- Non Handed (F8000 Series)
- Reversible (F8100 Series)

## FINISHES AVAILABLE

US CODE	DESCRIPTION
US28	Aluminum
US32D	Stainless Steel
DURO	Duro Bronze

## PRODUCT SPECIFICATIONS

**APPLICATIONS:** For offices, schools, hospitals, apartments, hotel/motels, and other public buildings.

**DOOR THICKNESS:** 1-3/4" ~ 2" standard, 2-1/4" optional.

**F8000 SERIES DOOR SIZE:** 33" to 36". Bar easily field cut to size.

**F8100 SERIES DOOR SIZE:** 33" to 36" x 84". Top Rod Extension available.

**STILE WIDTH:** 4-1/2" minimum stile width required for F8000 Series. 3-1/2" minimum stile width required for F8100 Series.

**CHASSIS, END CAP & RAIL ASSEMBLY:** Painted steel (Aluminum or Duro) or stainless steel (US32D) - Fire Grade Steel.  
**COVER:** Zinc Alloy

**LATCHBOLT:** Stainless with 3/4" throw (F8000 Series). Stainless (F8100 Series), Auxiliary Fire Latch (F8100-LBR Series).

**LATCHBOLT SPRING:** Stainless steel throughout.

**GUARD BOLT:** Stainless steel (F8000 Series only).

**F8000 SERIES STRIKE:** #8070 Steel Roller Strike - 2-3/4" or 2-3/8" Backset.

**F8100 SERIES STRIKE:** #8171 Steel Top Case and #8178 Steel Bottom Case.

**MOUNTING:** Furnished standard with wood & machine screws. Sex nuts and bolts (1346) standard.

**UL & ULC LISTED:** 3-Hour fire rating. Conforms to standards UL 10C and UBS 7-2-1997 codes.