



Creating Integrated Solutions
Since 1888

HEAVY DUTY CLEANERS

Formula 260

851 Progress Court Oakville, Ontario L6J 5A8
905-847-3000 Fax 905-847-1675

FORMULA 260 is a concentrated heavy-duty cleaner-degreaser for use in a wide variety of applications. It contains powerful synthetic detergents, a wetting agent, glycol ether solvent and alkaline builders.

FORMULA 260 is safe on most surfaces; it will not harm rubber, leather or plastic products. Use it on brick, heavy grease, on engines, motors, air filters, deep fat fryers, plastic surfaces, lighting fixtures, cars, trucks, bus washings, etc.

FEATURES

- Contains powerful synthetic detergents, wetting agent, glycol ether solvent and alkaline builders.
- Concentrated.
- Versatile cleaner.
- Non-explosive, non-flammable.
- Holds CFIA Letter of Non-Objection.
- Certified Kosher.

ADVANTAGES

- Effective on heavy build-ups of oil, grease and other soils.
- Can be used up to 1:40 for general cleaning; extended product coverage.
- Soak or spray applications and a variety of surfaces can be cleaned.

BENEFITS

- Versatile; quickly cleans metals, concrete, ceramic tile, painted surfaces, sealed wood, hard flooring etc.
- Economical.
- One product for many applications.
- For use in multiple locations.

Do not contaminate food, feed or potable water during use or storage of this product.

Food contact surfaces must be rinsed with potable water after use.

RECOMMENDED DILUTIONS

Parts F-260/Parts Water

- 1:1 For heavy grease and oil buildup on engines, engine parts, motors (shell only if electric), conveyors, machinery and other metal surfaces.
- 1:4 Piping, air conditioning ducts and grills. Greasy floors around machinery.
- 1:6 Terrazzo, concrete, wood, tile, ceramic (lot composition) floors, plastic and painted surfaces (not water-based paints).
- 1:8 Lighting fixtures, walls.
- 1:20 Steel files, lockers, partitions
- 1:40 General cleaning applications.

AVOID SOAKING ALUMINUM PARTS

TYPICAL PROPERTIES*

Appearance.....	Purple liquid
Odour.....	Lemon fragrance
Dissolution in water.....	Rapid
Specific gravity.....	1.038-1.042
Hard Water Tolerance.....	Stable
pH.....	12.5-13.5
Foaming.....	Moderate
Grease and oil removal.....	Outstanding
Flash Point.....	None
Soil Suspension.....	Excellent
Free alkali as caustic soda or caustic potash.....	None
Wetting action.....	Rapid
VOC% (EPA Method 24).....	10.5-11.5

*These values represent typical properties only, and are not to be construed as manufacturing specifications.

FOR HANDLING AND PRECAUTIONARY INFORMATION, REFERENCE THE PRODUCT LABEL AND MATERIAL SAFETY DATA SHEET.

Revision: 10/15/07
Supersedes: New

All data statements and information presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or implied warranty or merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.