

OHS, "OVERHEIGHT STOP", 51 x 18

MATERIALS

Extruded Aluminum 1.5" Sq.
Reinforced ¼" Aluminum Plate Corners
Face Material - ¼" Impact resistant Dark Black tinted polycarbonate.
Back Material - ¼" Alupalite Composite.

ELECTRICAL

6 inch OVERHEIGHT STOP, quad pixel (5x8)
12 VDC @ 2.6 Amps, approx. 31 Watts.
Operating Temp. -40 to +80 deg.C (-40 to +180 deg.F).
Optional 120VAC input Remote 35 Watt UL power supply provided.

LED's

RED 5mm Cree Hi-brightness 30 degree.
Message blanks out when turned off.

FINISH

Standard Black Powdercoat or Natural Aluminum Clear Coat.
Custom colors available on request.

PHYSICAL

Standard sign Sealed. IP65 weather tight.
Viewable 48w x 15h (Actual 51w x 18h x 1.75d)
16.5 Rear T-Slot Spacing (Center to Center T-Slot Top to Bottom)
IP65 weather tight.
Mounting - (4) movable S.S. 5/16-18 T-Slot Nuts in top(2) and bottom(2) slots.
Mounting Weight - 29lbs



Over Height Sign with Flashing Strobe's

©2015-2022