

TWO MOVING PARTS

THERE ARE ONLY TWO MOVING PARTS IN DN HAMMERS, RESULTING IN LOWER MAINTENANCE COSTS, GREATER DURABILITY AND RELIABILITY.



POWERFUL KOREAN ROCK BREAKERS FOR AUSTRALIAN CONDITIONS

QUALITY GURANTEED ROCK BREAKER

DN UTILISES HIGHEST QUALITY MATERIALS WHICH ARE MACHINED BY EXPERIENCED TECHNICIANS USING STATE-OF-THE-ART MANUFACTURING FACILITIES IN KOREA.



**DEMOLITION
NATION**

DISTRIBUTOR



**MAXIMUM
ROCK BREAKING
POWER**

TESTED AND PROVEN ROCK BREAKING POWER

DN HAMMERS INCORPORATE ENHANCED ROCK BREAKING POWER FROM TESTED AND PROVEN TECHNOLOGY OF HYDRAULIC ENERGY AND NITROGEN GAS ASSISTANCE.

SPECIFICATIONS OF DEMOLITION NATION HAMMERS

DN MODEL	BT10	BT20	BT35	BT40	BT55
Operating Weight (kg)	70	100	195	260	410
Oil Flow Rate (litre/min)	15-30	20-40	30-60	30-60	50-90
Setting Pressure (bar)	130	140	150	160	180
Operating Pressure (bar)	90-120	90-120	100-130	90-130	120-150
Impact Rate (bpm)	800-1400	700-1100	500-1000	450-750	400-800
Impact Energy (joule)	180	220	320	600	700
Hose Diameter (inch)	0.5	0.5	0.5	0.5	0.5
Tool Diameter (mm)	40	45	60	68	75
Applicable Carrier (ton)	0.7-1.8	1.2-3.0	2.5-4.5	4.0-7.0	6.0-8.0

