

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
255	STD	17-51	70-15	248	265	193	190	.256	.256	.420	.420	.028	.025	.015	.015	110	111	225
582	1	21-50	57-25	250	262	200	215	.264	.264	.437	.434			.012	.015	105	109	GAS
233	2	29-56	60-27	266	268	216	216	.265	.265	.436	.436	.050	.045	.015	.015	107	107	
439	2	36-70	72-36	286	288	215	219	.295	.295	.490	.488	.048	.045	.012	.014	108	112	
212	3	25-72	73-34	287	287	230	230	.277	.277	.456	.456	.065	.060	.015	.015	108	110	
107	4	32-68	68-30	280	278	228	227	.295	.295	.484	.484	.065	.058	.018	.018	108	108	
215	5	32-75	76-31	287	287	243	240	.292	.292	.481	.478	.075	.073	.015	.018	113	111	

CODE: CHRYSLER 225
 PERFORMANCE - 46G
 STANDARD - 46S
 BILLET - EP7
 EXCHANGE - DEP 225

SLANT 6-225

ROCKER RATIO 1.7

CHRYSLER