

KENWOOD

NEXEDGE®

NX-200/300ABP

NEXEDGE® VHF/UHF Digital & FM Portable Radios



*CSA Certified for Class I,
Division 1, Groups A & B

NXDN® **FleetSync®**
by KENWOOD

*CSA Certified for Class I, Division 1, Groups A, B, C, and D; Class II, Division 1, Groups E, F and G; Class III, Division 1: Class I, Division 2, Groups A, B, C, and D.

● GENERAL FEATURES

- 5 W (136-174 MHz) Models
- 5 W (406-470 MHz) Models
- 512 CH-GID / 128 Zones
- 12-Key Keypad Models
- 14 Character Alphanumeric Aliases
- Backlit Dot Matrix LCD
- 3-Digit Sub-Display
- Function/Status LCD Icons
- RSSI Indicator
- Date & 12/24 Hour Time Clock
- Transmit/Busy/Call Alert/Warn LED
- On/Off Volume Knob
- 16-Position Mechanical Selector
- 6 Front PF & Menu Keys
- 2 Side PF Keys
- Emergency/AUX Key
- 500 mW Speaker Audio
- VOX Ready
- Emergency Call Features
- Emergency Man-Down Option
- Lone Worker
- Multi-Language Display
- Programmable TX/RX Indication (On/Off)
- Special Alert Tone Patterns
- Time Out Timer
- Busy Channel Lockout
- LCD Battery Status Indicator
- Low Battery Alert
- Battery Saver
- Weather-sealed ACC Connector
- MIL-Spec Speaker Mic Options
- KMC-47GPS Speaker Mic Option
- KPG-111D Windows® FPU
- Flash Firmware Upgrading
- Front Panel Test & Tune
- Cloning
- MIL-STD-810 C/D/E/F
- MIL-STD "Driven-Rain"
- IP-54/55 Water & Dust Intrusion
- Easy Option Port
- PC Serial Interface
- SDM Manual Input¹
- Transparent Data Mode¹
- Intrinsically Safe Option
- VGS-1 Voice Guide/ Voice & GPS Data Storage Option

● DIGITAL – COMMON

- NXDN® Digital Air Interface
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Paging Call
- Emergency Call
- All Group Call
- Status Messaging¹
- Remote Stun/Kill¹
- Remote Check¹

- Short & Long Data Messages¹
- GPS Location with Voice¹
- NXDN® Scrambler Included

● DIGITAL – CONVENTIONAL MODE

- 64 Radio Access Numbers (RAN)
- DTMF (Encode/Decode)
- Individual & Group Selective Call
- Mixed FM/Digital Operation

● DIGITAL – TRUNKING MODE

- Individual Private Call
- Group Call
- Broadcast Call
- Transmission Trunked Mode²
- Message Trunked Mode²
- Call Queuing with Priority²
- Call Queue Pre-emption²
- Late Entry (UID & GID)²
- 4 Priority Monitor ID's²
- Remote Group Add¹
- Failsoft Mode
- Multi-Site IP Network Compatible

● SCAN

- Single Zone / Multi-Zone / List Scan
- Dual Priority Scan (Conventional)

● FM MODES – GENERAL

- 25 & 12.5 kHz Channels
- FleetSync®/II
- DTMF Encode / Decode
- Companded Audio
- Voice Inversion Scrambler
- Encryption/ANI Board Control

● FM CONVENTIONAL ZONES

- QT / DQT
- Two-Tone Decode
- Single/Two-Tone Encode
- Call Key 1-6
- Operator Selectable Tone

● FM LTR® TRUNKED ZONES

- Kenwood LTR® Features

● FleetSync®/II (FM)

- PTT ID Digital ANI
- Selective Call & Group Call
- Status Messaging¹
- Emergency Status
- Caller ID Display
- Short Text Messages¹
- Power On/Off Status Messages¹
- Send/Display GPS (KMC-47GPS)¹
- PTT ID & Emergency GPS Reporting¹
- Status Message Block GPS Reporting¹



Options

■ KNB-72LC*
Li-Ion Battery
(1880mAh)
CSA A&B Intrinsically Safe



■ KWD-YH20-NX2*
Yellow Housing

■ KWD-OH20-NX2*
Orange Housing

■ KSC-32
Tri-Chemistry Rapid
Rate Charger



■ KSC-326
Rapid Rate Six Unit Charger
for Ni-Cd/Ni-MH/Li-Ion



■ KMC-41D*
MIL-STD & IP 54/55
Speaker Microphone



■ KMC-47GPS*
GPS Speaker
Microphone



■ V4-10388*
Behind-the-Head
w/earcup PTT



■ KHS-15-BH*
Behind-the-Head
Heavyduty Headset

■ KEP-1*
Heavy Duty Earphone



■ KRA-22/23*
VHF/UHF Helical Antenna



■ KRA-26/27*
VHF/UHF Whip Antenna



■ KRA-28*
VHF Broadband
Antenna



■ KRA-29P*
UHF Broadband
Antenna



■ VGS-1*
Voice Guide
& Storage Unit



■ KWD-AE30/31*
Secure Cryptographic
Module



■ KBH-11*
Belt Clip (2.5")



* Refer to Intrinsically Safe / Non-Incendive Manual B59-2635-xx for listing of CSA IS approved accessories.

All accessories and options may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Main Specifications

		NX-200	NX-300
GENERAL			
Frequency Range	Type 1 Type 2	136-174 MHz	406-470 MHz
Number of Channels		512	
Zones		128	
Max. Channels per Zone			250
Channel Spacing	Analog Digital	12.5 / 15 / 25 / 30 kHz 6.25 / 12.5 kHz	12.5 / 25 kHz 6.25 / 12.5 kHz
Operating Voltage		7.5V DC $\pm$ 20%	
Battery Life (with KNB-72LC) 5-5-90		1W 13.75 Hrs / 2W 12.5 Hrs / 5W 10 Hrs.	
Operating Temperature Range		-22° F to +140° F (-30° C to +60° C)	
Frequency Stability		$\pm$ 2.0 ppm	$\pm$ 1.0 ppm
Antenna Impedance		50 Ω	
Dimensions (W x H x D)	Projections not included Radio only with KNB-72LC	2.28 x 5.02 x 1.63 in (58 x 127.5 x 41.3 mm) 2.28 x 5.02 x 1.91 in (58 x 127.5 x 48.5 mm)	
Weight (net)	Radio only with KNB-72LC	8.82 oz (250 g) 14.29 oz (405 g)	
IC Certification	Type 1 Type 2	282D-378400	282D-378500 282D-378501

		NX-200	NX-300
RECEIVER			
Sensitivity	Digital @ 6.25kHz (3% BER) Digital @ 12.5kHz (3% BER) Analog (12 dB SINAD)	0.20 μ V 0.25 μ V 0.25 μ V	
Selectivity	Analog @ 25 kHz Analog @ 12.5 kHz	72 dB 65 dB	
Intermodulation Distortion	Analog	70 dB ($\pm$ 50,100 kHz)	
Spurious Response	Analog	70 dB	
Audio Distortion		Less than 3%	
Audio Output		500 mW / 8 Ω	
TRANSMITTER			
RF Power Output		5 W / 1 W	
Spurious Response		70 dB	
FM Hum & Noise	Analog @ 25 kHz Analog @ 12.5 kHz	45 dB 40 dB	
Audio Distortion		Less than 3%	
Modulation		16K0F3E, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

Analog measurements made per TIA/EIA 603 and specifications shown are typical.
Specifications are subject to change without notice, due to advancements in technology.

FleetSync™ is a registered trademark of JVCKENWOOD Corporation.
AMBE+2™ is a trademark of Digital Voice Systems Inc.
Windows® is a registered trademark of Microsoft Corporation.
NXDN® is a registered trademark of JVCKENWOOD Corporation and Icom Inc.
NEXEDGE® is a registered trademark of JVCKENWOOD Corporation.
CSA® is a registered trademark of the Canadian Standards Association.

Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV
International Protection Standard				
Dust & Water Protection	IP54/55			

footnotes from Front:

¹ Requires NX subscriber unit PC Serial Interface compatible software application (e.g. Kenwood AVL & Dispatch Messaging software) or hardware (e.g. console).

² These trunked features are primarily system programming and operational dependent. Priority Monitor also requires NX subscriber settings.

KENWOOD

JVCKENWOOD warrants its transceivers for two years, one year on accessories. For further information please contact your local dealer or JVCKENWOOD Canada Inc.

JVCKENWOOD Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.com/ca



ISO9001 Registered
JVCKENWOOD Corporation

ADS#05916