4 and 6 Cylinder Mini Cars

- 1. Must be factory front wheel drive
- 2. ALL glass must be removed from vehicle-removing front windshield is optional
- 3. Doors can be wired, chained, or bolted shut.
 - a. Driver's door may be welded solid
- 4. Notching of frame is allowed—No reinforcing subframe and no added bolts or plates
- 5. Battery can remain in stock location, or moved to passenger side floorboard and securely fastened
- 6. Must have helmet, eye protectant and working seat belt
- 7. Stock bumpers only—No truck bumpers or fabricated bumpers
- 8. A 4-point cage inside of car is allowed, but cannot pass through firewall and cannot go further than 6" past driver's seat
- 9. Wire, bolt, or chain trunk in stock location
- 10. Aftermarket or sleeved tie rods allowed
- 11. Any wheel/tire combo allowed
- 12. No full frame cars
- 13. All cars must be clearly numbered on both sides and <u>TOP</u> of vehicle.
- 14. 4/6-cylinder front wheel drive minivans are allowed this year
- 15. Must have chain or heavy strap/wire must run from center of the roof to dashboard to act as a center post to prevent the hood from entering the driver's compartment
- 16. There needs to be a 16" inspection hole cut in the trunk and hood
- 17. Immediate Disqualification:
 - a. Breaching outside barrier
 - b. Ignoring and/or fighting with officials
 - c. non-compliance with rules
 - d. use of alcohol and/or illicit drugs
 - e. targeting driver's door
 - f. Fighting with other drivers
 - g. changing of parts after inspection that are not legal, including between heat and consolation or heat and main or consolation and main.
- 18. Body Creasing of rear quarter panel and V'ing of trunk lid is allowed