

<b>Project:</b>	
<b>Date:</b>	
<b>Note:</b>	

### LED LINEAR STRIP LIGHT 8' 64W TR12 SERIES



#### FEATURES & BENEFITS

- High lighting efficiency 130 lm/W, Ra≥80;
- Daisy connection with very convenient replacement in 1minute
- 1-10V dimmable driver, AC 120-277V;
- Available with suspending installation and surface-mounted installation;
- Wide application for: school, hospital, super market, office and warehouse;
- 5 years warranty.

#### APPLICATIONS

- Commercial: Stores, Offices and Hallways
- Industrial: Lower Ceiling Warehouses, Manufacturing
- Retail: Stores, Storage Areas and Closets
- Residential: Garages



SPECIFICATIONS		TR12-64W-240-40K-PDN-A	TR12-64W-240-50K-PDN-A
<b>Ordering</b>	Brand	Builders Pack	Builders Pack
	SKU	57-55056-40	57-55056-50
<b>Photometric</b>	Color Temp. [CCT]	4000K	5000K
	Lumens [lm]	8394.50 lm	8482.24 lm
	Efficacy [lm/W]	132.42 lm/W	133.81 lm/W
	SDCM	≤6	
	Render Index [Ra]	≥80	
	R9	≥0	
	Duv	≤0.006	
<b>Electrical</b>	Beam Angle	120°	
	Rated voltage	AC 120-277V	
	Frequency	50/60Hz	
	Lamp wattage	64W	
	Lamp current	640mA	
<b>Lifetime [at 120-227V]</b>	Power factor	≥0.9	
	L70 Lumen maintenance life [Hours]	≥50000	
	L90 Lumen maintenance life [Hours]	≥36000	
<b>Technical Requirements</b>	Warranty [years]	5	
	Certifications	UL: E491816   RoHS   FCC   CE	
	THD	≤20%	
	Ripple Current	≤5%	

# LIBERTY LED LLC

<b>Project:</b>	
<b>Date:</b>	
<b>Note:</b>	

**SIMPLY RELIABLE**

	Frequency of LED current	≥120Hz
	Flicker	No Flicker
	Electrostatic Discharge 【ESD】	4KV Contact discharge / 8KV Air discharge
	Surge Protection	2KV
	Dimming	1-10V
	Sensor	Optional
	Emergency Power	Optional
	Ingress Protection 【IP】	IP20
	Noise	N/A
<b>Operation and information</b>	Start time	≤1 S
	Operating Temp.	-4°F+113°F
	Storage Temp.	-22°F+149°F
	Housing/Case 【color,material】	White / Steel
	Optical -Lens 【material】	PC Cover
	Mounting / Installation	Pendant Mounted / Surface Mounted
	Environment	Indoor / Suitable for damp location
<b>Dimensions</b>	Product Size 【LWH】	95.98"×2.95"×3.39"
	Gross Weight	32.50 lbs






<b>Shipping</b>	Pcs / Carton	4pcs
	Master Carton Size	97.40" x 7.48" x 8.66"
	Pcs / Pallet	104pcs
	Pcs / 20' GP	1080pcs (No Pallet)   720pcs (Palletized)
	Pcs / 40' GP	2164pcs (No Pallet)   1620pcs (Palletized)
	Pcs / 40' HQ	2628pcs (No Pallet)   1620pcs (Palletized)
	Pcs / 45' HQ	2900pcs (No Pallet)   1800pcs (Palletized)

\*Package specifications are subject to change without notice.

## LAMP CODE DEFINITIONS

Internal Use	Wattage	Size	CCT	DLC Degree	Dimmable	Sensor	Flicker
TR12	64W	240 = 8FT	XXK=40K,50K	P = Premium	D = 1-10V	N=No Sensor	N=No Flicker

<b>Project:</b>	
<b>Date:</b>	
<b>Note:</b>	

ACCESSORIES		
SKU	Description	Image
57-55110-A	Connection kit Surface mounting	
57-55112-A	Suspending kit Suspending Installation	
57-55114-A	Connection kit Suspending Installation	
57-55116-A	Built-in Microwave Sensor	
57-55117-A	8W Built-in Emergency Driver,90 Minutes	
79-92014	15w Emergency Power	